

DEPARTMENT

City Comptroller

**Community Development** 



DATE FORWARDED TO NEXT DEPT.

Initials

KB

Contract 20/90357

# **City of Springfield Contract Tracer Document**

The purpose of this document is to provide continuous responsibility for the custody of **CONTRACTS** during the processing period.

DATE RECEIVED
Initials

**INSTRUCTIONS:** Upon receipt, please initial and write in the date of receipt. When your department has approved and signed the contract, please initial and date in the forwarding section and deliver to the next department.

Date

CAFO	77	11.4.5	TH	
Law	4mm	1114/8	amm	1/1/6/18
Mayor	mm	11-16-18	1313	11-16-181
City Comptroller	NOS	11/19/18	MG	11/19/18
<b>Community Development</b>		1. (.		/
Vendor No.: 18470 Contract No.: Contract Date: 10/19/2018  21/90357  Contract Amt.: \$70,965.00 Issue Date: 11/7/18 Renewal Date:				
Appropriation Code1: 26451815-530105-64516 Appropriation Code2: Appropriation Code3: Appropriation Code4:				
Description of Funding Source: CDBG-NDR				
Bid No.: Requisition No.: 19006683 PO No.:				
Vendor Name: Kristian Berrios Torres & Marisabel Gonzalez-Borges				
Contract Type: CDBG-NDR Healthy Homes Rehab				
Contract Purpose: Rehabilitation of Home located at 58 Bancroft Street, Spfld, MA				
Originating Dept.: Community Development				
Expiration Date: 12/3/20	023 Amendm	ent Date:	Extension Date:	
TYPE OF DOCUMENT (Ple  ☑ New ☐ Renewa			tension	

# CITY OF SPRINGFIELD

# HEALTHY HOMES REHABILITATION PROGRAM AGREEMENT FOR OWNER-OCCUPANTS

Whereas, Kristian Berrios Torres and Marisabel Gonzalez-Borges ("Homeowner") are receiving Healthy Homes Rehabilitation Program financial assistance from the City of Springfield ("City") in the amount of \$70,965 to fund rehabilitation of the home located at 58 Bancroft Street according to the terms of the agreed-upon Work Write-Up Specifications and in compliance with Massachusetts and City of Springfield building and health codes. The Healthy Homes program is funded by the federal Community Development Block Grant-National Disaster Resilience (CDBG-NDR) program.

Now, therefore, the parties agree as follows:

# Terms of the Loan

Financial assistance is provided as a 0% interest, five-year, forgiveable loan. As long as the Homeowner complies with this Agreement, the principal amount of the loan shall be forgiven at an equal percentage rate of 20% per full year plus 45 days until it is 100% forgiven after five years plus 45 days.

#### **Owner Occupancy**

The Homeowner will use the home as their principal residence for a period of five years plus 45 days following final payment to the contractor the event that the Borrower continues to own the property, but fails to maintain it as a principal place of residence for the five—year loan term referenced above, the entire sum of the loan will become immediately due and payable.

The Homeowner understands that if, during the five-year loan term, part or all of the property is sold or refinanced without the City's prior written consent, the City shall require payment in full the amount of the loan outstanding at time of sale.

#### **Rental Units**

If the property has multiple units, the Homeowner must live in one unit and rent any other units to households with income at or below 80% area median income (AMI) for the five-year loan period. The AMI amount changes from year to year; the required income limits can be obtained from the Springfield Office of Housing.

The Homeowner may not evict existing tenants without cause for a period of two years, following final payment to the contractor.

Mores

# **Income Eligibility**

The Homeowner certifies that he/she has provided complete, accurate, and current information regarding household income to demonstrate Homeowner's eligibility to receive CDBG-NDR funds.

#### Enforcement

The Homeowner and the City acknowledge that the City has the right and responsibility to enforce this agreement.

This contract is signed as of the \_\_\_\_\_ day of October, 2018.

11/8/18

Kristian Berrios-Torres, Borrower

Geraldine McCafferty, Director Director, Office of Housing CITY OF SPRINGFIELD

Marisabel Gonzalez-Borges, Borrower

W 24451815-630105-44516 \$70,965.00

Approved as to Appropriation:

Approved as to Form:

Office of Comptroller

Law Department

APPROVED:

Chief Administrative and Einancial Officer

Jamonica Sarna Mayor



# **MORTGAGE**

City of Springfield Healthy Homes Rehabilitation Program

THIS MORTGAGE is made as of October 19, 2018, between Kristian Berrios Torres and Marisabel Gonzalez-Borges, whose address is 58 Bancroft Street ("Borrower"), and the City of Springfield, a municipal corporation with the address 36 Court Street, Springfield, Massachusetts ("City").

WHEREAS, the Borrower and the City entered into a **HEALTHY HOMES REHABILITATION PROGRAM AGREEMENT** dated October  $\bigcirc$  2018 in the sum of \$70,965 (the Principal Amount"), together with interest of 0%, (this indebtedness is called the "**Note**", a copy of which is attached to this Mortgage as **Schedule A**); and

WHEREAS, to secure the performance of all the terms, covenants, agreements, conditions and obligations of the Note and this Mortgage, the Borrower wishes to grant to the City its rights, title, and interest in the property located at 58 Bancroft Street in Springfield, Massachusetts and described on the attached **Schedule B** (the "Mortgaged Property").

NOW THEREFORE, in consideration of the loan for the Principal Amount made by the City to the Borrower, the Borrower and the City hereby agree as follows:

 Purpose. This Mortgage and the Note are to secure a loan made by the City to the Borrower for the purpose of making home improvements to the Mortgaged Property, as detailed in the Work Write-Up Specifications dated 3/9/2018. The Borrower is responsible for making the improvements, and the City shall only make payment of Principal for such improvements as it inspects and verifies that the improvements have been completed.

# 2. Conditions of the Loan.

- a. Due Upon Sale or Transfer. If the Borrower sells or transfers the Mortgaged Property before the final maturity date, the amount of the loan still owing at the time of sale or transfer will be immediately due and payable to the City.
- b. Owner Occupancy. If the Borrower is an owner-occupant at the time this loan is entered into, the Borrower must continue to live in the Mortgaged Property as his/her principal place of residence during the term of the loan.

Mas

c. Rental Unit Affordability. If the Borrower (including a Borrower who lives in one unit of a multi-unit property) rents out units in the Mortgaged Property to others, the Borrower must rent all units in the Mortgaged Property to households with income at or below 80% of the area median income<sup>1</sup> during the term of the loan.

#### 3. Terms of the Loan

Loan Type:

Forgivable loan, due upon default or upon

sale or transfer of property prior to final maturity

Interest Rate:

0%

Payment Schedule:

No monthly payments

Final Maturity Date:

5 years from date of execution

Forgiveness:

An equal amount of the loan will be forgiven for each year

that passes from the date the loan is entered, until the

loan is fully forgiven at the final maturity date.

(For example, a 5-year loan is forgiven 20% per year;

a 10-year loan is forgiven 10% per year.)

Prepayment penalty:

None

- 4. Completion of Agreed-Upon Improvements. If construction required to meet the Work Write-Up Specifications is discontinued or not carried out with reasonable diligence, the City after due notice to the Borrower is authorized to enforce or carry out existing contracts between the Borrower and other parties to make contracted improvements, to make and enter into additional contracts and incur obligations for the purposes of completing the improvements, and to pay and discharge all debts, obligations and liabilities incurred by reason of any action taken by the City, the cost of which shall be payable from the Borrower to the City on demand and shall be secured by this Mortgage.
- 5. **Compliance with Building and Health Codes**. The improvements shall comply with all applicable municipal and state ordinances, laws, regulations, and rules made or promulgated by lawful authority, and upon their completion shall comply therewith and with the rules of the Board of Fire Underwriters having jurisdiction.
- 6. Payment of Property Taxes and Other Charges. The Borrower will pay when due all taxes, assessments, water & sewer charges, and other governmental charges, fines and

<sup>&</sup>lt;sup>1</sup> The area median income (AMI) for the Springfield Metropolitan Area is established annually by the U.S. Department of Housing and Urban Development. The Springfield Office of Housing will provide the current AMI for the Springfield Metropolitan area upon request.

impositions, now or hereafter imposed, on the Mortgaged Property and will pay when due every amount of indebtedness secured by any lien on the Mortgaged Property.

7. Maintenance and Repair. The Borrower shall maintain the Property and shall not allow the property to deteriorate or decrease in value due to its condition. If the Property is damaged, the Borrower shall promptly repair the Property to avoid further deterioration or damage, unless repair or restoration is not economically feasible. The Borrower shall not commit waste or permit others to permit actual, permissive, or constructive waste on the Property.

#### 8. Property Insurance.

a. Maintenance of Insurance. The Borrower shall keep the Property insured against loss by fire, earthquakes, floods, hazards included within the term "extended coverage," and any other hazards for which the City requires insurance. The insurance amounts (including deductible levels) and periods and the insurance carrier shall be subject to the City's approval. Unless otherwise required by the City, all such insurance shall be effected by Standard Fire and Extended Coverage Insurance policies, in amounts not less than necessary to comply with the coinsurance clause percentage of the value applicable to the location and character of the property to be covered.

All such property insurance shall be in such form and shall have attached loss payable clauses in favor of the City. All such policies and attachments shall be delivered promptly to the City, unless they are required to be delivered to the holder of a lien of a mortgage or similar instrument to which this Mortgage is expressly subject, in which case a certificate of insurance shall be delivered to the City. The Borrower will pay any and all premiums on such insurance promptly when due.

b. City Rights to Payment for Loss or Damage. In the event of loss or damage to the mortgaged property, the Borrower will give to the City immediate notice of the event and the City may make and file proof of loss if not made otherwise promptly by or on behalf of the Borrower. Each insurance company issuing any such policy is authorized and directed to make payment under the policy for such loss to the Borrower and the City jointly, unless the amount of loss is payable first to the holder of a lien under a mortgage or similar instrument to which this Mortgage is expressly subject. Insurance proceeds received by the City may be applied, at the City's option, either in reduction of the indebtedness

secured by this Mortgage, or to the restoration or repair of the damaged Mortgage Property.

- 9. **Rights of City as Lender**. If the Borrower fails to carry out the covenants and agreements set forth in this mortgage, the City may do and pay for whatever is necessary to protect the value of and the City's rights in the property, and any amounts so paid shall be added to the Principal amount due to the City hereunder
- 10. **Inspection.** The City shall have the right to inspect the Mortgaged Property from time to time at any reasonable hour of the day.
- 11. Acceleration upon Default. If any condition of this Mortgage shall be in default, the entire outstanding balance of the Principal Amount shall become immediately due and payable at the option of the City. The City shall be entitled to collect all costs and expenses, including reasonable attorney's fees incurred. If the City exercises its option to require immediate payment of the balance of funds secured by this Mortgage, the City shall give Borrower notice of acceleration. This notice shall provide a period of not less than 30 days from the date the notice is delivered or mailed within which Borrower must pay all remaining sums secured by the Mortgage.

The following "events of default" will cause the Note to be immediately due and payable:

- a. The Borrower's nonperformance of any covenant, agreement, term, or condition of this Mortgage or of the Note, after the Borrower has been given due notice by the City of such nonperformance;
- b. The Borrower's failure to perform any covenant, agreement, term, or condition in any Mortgage or instrument creating a lien upon the Mortgaged Property, which lien shall have priority over the lien of this mortgage;
- c. The City's discovery that the Borrower failed to disclose in the Borrower's application for funds any fact deemed to be material by the City, or that the Borrower made any misrepresentations in the application or in any agreements entered into between the Borrower and the City (including but not limited to, the Note and this Mortgage);
- d. The sale, lease or other transfer of any kind or nature of the Mortgaged Property, or any part thereof, without the prior written consent of the City.

- 12. **No waiver**. No party shall be deemed to have waived any provision of this Mortgage or the exercise of any rights under this Mortgage unless such waiver is made expressly and in writing. Waiver by any party of a breach or violation of any provision of this Mortgage shall not constitute a waiver of any other subsequent breach or violation.
- 13. Surrender after Default. If the Borrower defaults, and upon demand from the City, the Borrower shall immediately surrender possession of the Mortgaged Property to the City, and the City may enter such property, rent out and collect rent from Mortgaged Property units, and apply rental income to the indebtedness secured by this Mortgage. The City may also dispossess, by usual summary proceedings, any tenant defaulting in the payment of any rent to the City. The Borrower shall cooperate and facilitate any summary process proceedings under this paragraph.

If the Borrower continues to occupy the Mortgaged Property after default and City demand to surrender, such possession shall be as a tenant of the City, and the Borrower shall pay in advance upon demand by the City, a reasonable monthly use and occupancy fee for the premises occupied by the Borrower, and upon the failure of the Borrower to pay such monthly fee, the Borrower may also be disposed by the usual summary proceedings applicable to tenants.

This covenant shall become effective immediately upon the happening of any such default, as determined in the sole discretion of the City, who shall give notice of such determination to the Borrower; and in the case of foreclosure and the appointment of a receiver of the rents, the within covenant shall insure to the benefit of such receiver.

14. **Notice of Change of Ownership**. The Borrower will give immediate notice by certified mail, return-receipt requested, to the City of any conveyance, transfer or change in ownership of such property, or any part thereof.

# 15. No Assignment of Rents.

The Borrower will not assign the rents, if any, in whole or in part, from the mortgaged property, or any part thereof, without the prior written consent of the City.

- 16. **Notice**. Notice and demand or request shall be made in writing and may be served in person or by mail.
- 17. Waiver of Homestead Exemption. The Borrower hereby waives the benefit of all homestead exemptions, as to the debt secured by this Mortgage and as to any



expenditure for insurance, taxes, levies, assessments, dues or charges incurred by the City pursuant to any provision of this Mortgage.

- 18. City Right to Nonjudicial Foreclosure. This Mortgage is upon the STATUTORY CONDITION, for any breach of which, or for breach of any of the aforementioned provisions or conditions, the City may declare all sums secured hereby immediately due and payable, and the City shall have the STATUTORY POWER OF SALE.
- 19. Joint and several liability. If the Borrower, as defined herein, consists of two or more parties, this Mortgage shall constitute a grant and mortgage by all of them jointly and severally, and they shall be obligated jointly and severally under all the provisions hereof and under the Note.
- 20. **Discharge**. Upon payment in full by the Borrower of the Note and any other instruments secured by this Mortgage, this Mortgage shall be terminated, and the City shall provide the Borrower the appropriate notice of termination.

**IN WITNESS THEREOF** this mortgage has been duly signed and sealed by the Borrower on or as of the day and year first above written.

Kristian Berrios Torres

Marisabel Gonzalez-Borges

Witness

me

Laviam Manus By.

On 10/19/18, before m Kylstian Berrus Torres	ne, the undersigned notary public, personally appeared,  vd Harisabel Gonzaliz – Borse,  proved to me through satisfactory evidence of
identification, which was YA	
person whose name is signed on the	e preceding or attached document, and acknowledged to
methat he/she signed it voluntarily f	or its stated purpose.
$I \sim$	
	(Official signature and seal of notary).
LAURA M. MARINO Notary Public COMMONWEALTH OF MASSACHUSETTS My Commission Expires On May 16, 2025	Notary Public: Lawra M. Manw, Cty. My Commission Expires: 5/16/a5

The note secured by this Mortgage has:

A principal sum of \$Click here to enter text.. A rate of interest of Zero (0%) percent.

The sum of \$70,965.00 . with interest thereon at a rate of Zero (0.00%) per annum, is due and payable upon sale, lease or other transfer of any kind of the above-referenced property, or any part thereof without the prior written consent of the City, other than a transfer by will or by operation of the laws of descent and distribution.

# SCHEDULE A PROMISSORY NOTE

Click here to enter a date.

Springfield, Massachusetts

Property Address: Click here to enter text., Springfield, MA

# 1. BORROWERS' PROMISE TO PAY

In return for a loan that I have received, I, Click here to enter text. ("Borrower"), promise to pay \$Click here to enter text. (this amount is called "Principal"), without interest, to the **City of Springfield**, a Massachusetts municipal corporation with a usual address of 36 Court Street, Springfield, Massachusetts 01103 ("City").

#### INTEREST

Interest will not be charged on unpaid principal.

# 3. TIME AND PLACE OF PAYMENTS

No monthly payments are due. If there is no default on the loan, the Principal shall be forgiven at an equal percentage rate per year until it is 100% forgiven at the end of the Click here to enter text.year.

#### 4. BORROWER'S RIGHT TO PREPAY

I have the right to make payments of principal at any time before they are due. A payment of principal only is known as a "prepayment." When I make a prepayment, I will tell the City in writing that I am doing so.

I may make a full prepayment or partial prepayments without paying any prepayment charge. The City will use all of my prepayments to reduce the amount of principal that I owe under this Note. If I make a partial prepayment, there will be no changes in the due date or in the amount of my payment unless the City agrees in writing to those changes.

# 6. BORROWER DEFAULT

(A) Default If I am in default of or breach of the Healthy Homes Rehabilitation Program Agreement ("Program Agreement") or the Mortgage, both dated the same date as this Note, and if I do not cure any default or breach within any applicable cure period, then I will be in default of this Note.

My

- (B) Notice of Default If I am in default, the City may send me a written notice telling me that if I do not come into compliance with the Program Agreement and Mortgage by a certain date, the City may require me to pay immediately the full amount of principal I owe.
- (C) No Waiver by City Even if, at a time when I am in default, the City does not require me to pay immediately in full as described above, the City will still have the right to do so if I am in default at a later time.
- (D) Payment of City's Costs and Expenses If the City has required me to pay immediately in full as described above, the Note Holder will have the right to be paid back by me for all of its costs and expenses in enforcing this Note to the extent not prohibited by applicable law. Those expenses include, for example, reasonable attorneys' fees, court costs and witness fees, including but not limited to expert witness fees.

# 7. GIVING OF NOTICES

Unless applicable law requires a different method, any notice that must be given to me under this Note will be given by delivering it or mailing it by first class mail to me at the Property Address above or at a different address if I give the City a notice of my different address.

Any notice that must be given to the City under this Note will be given by mailing it by first class mail to:

Director

City of Springfield Office of Housing

1600 E. Columbus Ave.

Springfield, MA 01103

with a copy simultaneously mailed by first class mail to:

City Solicitor
City of Springfield Law Department
36 Court Street
Springfield, MA 01103

# 8. OBLIGATIONS OF PERSONS UNDER THIS NOTE

If more than one person signs this Note, each person is fully and personally obligated to keep all of the promises made in this Note, including the promise to pay the full amount owed. Any

MORN

person who is a guarantor, surety or endorser of this Note is also obligated to do these things. Any person who takes over these obligations, including the obligations of a guarantor, surety or endorser of this Note, is also obligated to keep all of the promises made in this Note. The City may enforce its rights under this Note against each person individually or against all of us together. This means that any one of us may be required to pay all of the amounts owned under this Note. This Note is binding on me and my executors, administrators, heirs, successors and assigns.

#### 9. WAIVERS

I and any other person who has obligations under this Note waive the rights of presentment and notice of dishonor. "Presentment" means the right to require the City to demand payment of amounts due. "Notice of dishonor" means the right to require the City to give notice to other persons that amounts due have not been paid.

#### 10. UNIFORM SECURED NOTE

This Note is a uniform instrument with limited variations in some jurisdictions. In addition to the protections given to the City under this Note, a Mortgage dated the same date as this Note protects the City from possible losses which might result if I do not keep the promises which I make in this Note. That Mortgage describes how and under what condition I may be required to make immediate payment in full of all amounts I owe under this Note. Some of those conditions are described as follows:

**Due Upon Sale or Transfer.** If all or any part of the Property or any interest in it is sold or transferred without the City's prior written consent, the City may, at its option, require immediate payment in full of all sums secured by the Mortgage.

Owner Occupancy. If the Borrower is an owner-occupant at the time this loan is entered into, and the Borrower ceases to live in the Mortgaged Property as his/her principal place of residence during the term of the loan, the City may, at its option, require immediate payment in full of all sums secured by the Mortgage.

Rental Unit Affordability. If the Borrower (including a Borrower who lives in one unit of a multi-unit property) rents out units in the Mortgaged Property to others, and the Borrower rents units to households with income above 80% area median income, the City may, at its option, require immediate payment in full of all sums secured by the Mortgage.

My

If the City exercises its option to require immediate payment of the balance of funds secured by the Mortgage, the City shall give Borrower notice of acceleration. This notice shall provide a period of not less than 30 days from the date the notice is delivered or mailed within which Borrower must pay all remaining sums secured by the Mortgage.

EXECUTED as a sealed instrument as of the date first written above.

<u>-</u>
3

rely

# SCHEDULE B PROPERTY DESCRIPTION

That certain piece and parcel of land located in the City of Springfield, County of Hampden and more particularly described as follows:

Bounded southerly by Bancroft Street Fifty (50) feet; Easterly by land now or formerly of the Heirs of Henry W. Barrett, and Amelia E. Barrett, about one hundred and seventy three (173) feet; Northerly by a passageway about fifty (50) feet, and Westerly by land now or formerly of George A. Williams about one hundred seventy three (173) feet.

Being lot #29 on plan of lots recorded in Book 216, Page 601.

Being the land with the buildings thereon located at 58 Bancroft Street, Springfield, Massachusetts.

I the mortgagor's, Kristian Berrios Torres, expressly reserve my right of Homestead and do not wish to terminate my Homestead by granting the within conveyance notwithstanding my waiver of such homestead in paragraph 24 of the within mortgage.

Being the same premises conveyed to mortgagors by deed recorded herewith.

# SCHEDULE A PROMISSORY NOTE

Click here to enter a date.

Springfield, Massachusetts

Property Address: Click here to enter text., Springfield, MA

# 1. BORROWERS' PROMISE TO PAY

In return for a loan that I have received, I, Click here to enter text. ("Borrower"), promise to pay \$Click here to enter text. (this amount is called "Principal"), without interest, to the **City of Springfield**, a Massachusetts municipal corporation with a usual address of 36 Court Street, Springfield, Massachusetts 01103 ("City").

#### 2. INTEREST

Interest will not be charged on unpaid principal.

# 3. TIME AND PLACE OF PAYMENTS

No monthly payments are due. If there is no default on the loan, the Principal shall be forgiven at an equal percentage rate per year until it is 100% forgiven at the end of the Click here to enter text.year.

# 4. BORROWER'S RIGHT TO PREPAY

I have the right to make payments of principal at any time before they are due. A payment of principal only is known as a "prepayment." When I make a prepayment, I will tell the City in writing that I am doing so.

I may make a full prepayment or partial prepayments without paying any prepayment charge. The City will use all of my prepayments to reduce the amount of principal that I owe under this Note. If I make a partial prepayment, there will be no changes in the due date or in the amount of my payment unless the City agrees in writing to those changes.

# 6. BORROWER DEFAULT

(A) Default If I am in default of or breach of the Healthy Homes Rehabilitation Program Agreement ("Program Agreement") or the Mortgage, both dated the same date as this Note, and if I do not cure any default or breach within any applicable cure period, then I will be in default of this Note.

My

- (B) Notice of Default If I am in default, the City may send me a written notice telling me that if I do not come into compliance with the Program Agreement and Mortgage by a certain date, the City may require me to pay immediately the full amount of principal I owe.
- (C) No Waiver by City Even if, at a time when I am in default, the City does not require me to pay immediately in full as described above, the City will still have the right to do so if I am in default at a later time.
- (D) Payment of City's Costs and Expenses If the City has required me to pay immediately in full as described above, the Note Holder will have the right to be paid back by me for all of its costs and expenses in enforcing this Note to the extent not prohibited by applicable law. Those expenses include, for example, reasonable attorneys' fees, court costs and witness fees, including but not limited to expert witness fees.

# 7. GIVING OF NOTICES

Unless applicable law requires a different method, any notice that must be given to me under this Note will be given by delivering it or mailing it by first class mail to me at the Property Address above or at a different address if I give the City a notice of my different address.

Any notice that must be given to the City under this Note will be given by mailing it by first class mail to:

Director
City of Springfield Office of Housing
1600 E. Columbus Ave.
Springfield, MA 01103

with a copy simultaneously mailed by first class mail to:

City Solicitor
City of Springfield Law Department
36 Court Street
Springfield, MA 01103

# 8. OBLIGATIONS OF PERSONS UNDER THIS NOTE

If more than one person signs this Note, each person is fully and personally obligated to keep all of the promises made in this Note, including the promise to pay the full amount owed. Any

Money

person who is a guarantor, surety or endorser of this Note is also obligated to do these things. Any person who takes over these obligations, including the obligations of a guarantor, surety or endorser of this Note, is also obligated to keep all of the promises made in this Note. The City may enforce its rights under this Note against each person individually or against all of us together. This means that any one of us may be required to pay all of the amounts owned under this Note. This Note is binding on me and my executors, administrators, heirs, successors and assigns.

# 9. WAIVERS

I and any other person who has obligations under this Note waive the rights of presentment and notice of dishonor. "Presentment" means the right to require the City to demand payment of amounts due. "Notice of dishonor" means the right to require the City to give notice to other persons that amounts due have not been paid.

#### 10. UNIFORM SECURED NOTE

This Note is a uniform instrument with limited variations in some jurisdictions. In addition to the protections given to the City under this Note, a Mortgage dated the same date as this Note protects the City from possible losses which might result if I do not keep the promises which I make in this Note. That Mortgage describes how and under what condition I may be required to make immediate payment in full of all amounts I owe under this Note. Some of those conditions are described as follows:

**Due Upon Sale or Transfer.** If all or any part of the Property or any interest in it is sold or transferred without the City's prior written consent, the City may, at its option, require immediate payment in full of all sums secured by the Mortgage.

Owner Occupancy. If the Borrower is an owner-occupant at the time this loan is entered into, and the Borrower ceases to live in the Mortgaged Property as his/her principal place of residence during the term of the loan, the City may, at its option, require immediate payment in full of all sums secured by the Mortgage.

Rental Unit Affordability. If the Borrower (including a Borrower who lives in one unit of a multi-unit property) rents out units in the Mortgaged Property to others, and the Borrower rents units to households with income above 80% area median income, the City may, at its option, require immediate payment in full of all sums secured by the Mortgage.

My

If the City exercises its option to require immediate payment of the balance of funds secured by the Mortgage, the City shall give Borrower notice of acceleration. This notice shall provide a period of not less than 30 days from the date the notice is delivered or mailed within which Borrower must pay all remaining sums secured by the Mortgage.

EXECUTED as a sealed instrument as of the date first written above.

Borrower Kristian Berrios Torres Wilness Lawram. Manus in	•
Borrower Marisabel Gonzalez - Witness Borges	
COMMONWEALTH OF MASSACHUSETTS	
On this day of	raliz- Borge

reley

# SCHEDULE B PROPERTY DESCRIPTION

That certain piece and parcel of land located in the City of Springfield, County of Hampden and more particularly described as follows:

Bounded southerly by Bancroft Street Fifty (50) feet; Easterly by land now or formerly of the Heirs of Henry W. Barrett, and Amelia E. Barrett, about one hundred and seventy three (173) feet; Northerly by a passageway about fifty (50) feet, and Westerly by land now or formerly of George A. Williams about one hundred seventy three (173) feet.

Being lot #29 on plan of lots recorded in Book 216, Page 601.

Being the land with the buildings thereon located at 58 Bancroft Street, Springfield, Massachusetts.

I the mortgagor's, Kristian Berrios Torres, expressly reserve my right of Homestead and do not wish to terminate my Homestead by granting the within conveyance notwithstanding my waiver of such homestead in paragraph 24 of the within mortgage.

Being the same premises conveyed to mortgagors by deed recorded herewith.

#### TRUTH IN LENDING DISCLOSURE STATEMENT

DATE: October 2018

Loan Applicant(s): Kristian Berrios Torres and Marisabel Gonzalez-Borges

Loan Secured by Mortgage Covering Property at 58 Bancroft Street, Springfield, MA 01107

**AMOUNT FINANCED**: \$70,695

#### **TOTAL OF PAYMENTS:**

The total amount financed (and secured by the Mortgage) shall, at the option of the Lender, become **immediately due and payable in full** if:

- The Borrower fails to continue to use the property as his/her principal residence.
- The Borrower fails to make rental units at the property available to households with income at or below 80% of area median income.

Any financed amount that has not been forgiven pursuant to the terms of the Agreement, Note, and Mortgage, shall, at the option of the Lender, become <u>immediately due and payable in full</u> if there is a sale or transfer of the mortgaged property.

FINANCE CHARGE: \$ 0.00

MORTGAGE CLOSING COSTS: \$ 175.00 - recording fee

**DUE DATE:** See above, at Total of Payments.

FINAL MATURITY: 45 days after the final disbursement of Principal to Borrower

I/we acknowledge receipt of a copy of this statement on October 2018.

Kristian Berrios Torres

Witness

Witness

Witness

# TRUTH IN LENDING DISCLOSURE STATEMENT

DATE: October 4, 2018

Loan Applicant(s): Kristian Berrios Torres and Marisabel Gonzalez-Borges

Loan Secured by Mortgage Covering Property at 58 Bancroft Street, Springfield, MA 01107

**AMOUNT FINANCED: \$70,695** 

#### **TOTAL OF PAYMENTS:**

The total amount financed (and secured by the Mortgage) shall, at the option of the Lender, become **immediately due and payable in full** if:

- The Borrower fails to continue to use the property as his/her principal residence.
- The Borrower fails to make rental units at the property available to households with income at or below 80% of area median income.

Any financed amount that has not been forgiven pursuant to the terms of the Agreement, Note, and Mortgage, shall, at the option of the Lender, become <u>immediately due and payable in full</u> if there is a sale or transfer of the mortgaged property.

FINANCE CHARGE: \$ 0.00

**MORTGAGE CLOSING COSTS:** \$ 175.00 - recording fee

**DUE DATE:** See above, at Total of Payments.

FINAL MATURITY: 45 days after the final disbursement of Principal to Borrower

I/we acknowledge receipt of a copy of this statement on October 2018.

Kristian Berrios Torres

Witness

# **NOTICE OF RIGHT OF RESCISSION**

	10	
Date:	October 2018	
Amount Financed:	\$70,965	
Precomputed Finance Charge:	\$0.00	
Total Payments:	0	
Mortgage of Property situated at:	58 Bancroft Street, Springfield 01107	
Notice to Customer Required by L	aw:	
You have entered into a transaction on which may result in a lien, mortgage, or other security interest on your home. You have a legal right under the law to cancel this transaction, if you desire to do so, without any penalty or obligation within three business days from the above date or any later date on which all material disclosures required under the <b>Truth in Lending Act</b> have been given to you. If you so cancel the transaction, any lien, mortgage or other security interest on your home arising from this transaction is automatically void. You are also entitled to receive a refund of any down payment or other consideration if you cancel. If you decide to cancel this transaction, you may do so by notifying		
	CITY OF SPRINGFIELD Office of Housing	
	1600 E. Columbus Ave.	
	Springfield, MA 01103	
by mail or telegram sent not later than midnight of October, 2018. You may also use any other form of written notice identifying the transaction if it is delivered to the above address not later than that time. This notice may be used for that purpose by dating and signing below.		
	I hereby cancel this transaction.	

Kristian Berrios Torres

Marisabel Gonzalez-Borges

Date

Date

Receipt is herewith acknowledged of the foregon the undersigned customer(s) having received to 20	witness: Witness: May am . Ma
Marisabel Gonzalez-Borges	WITNESS:
EFFECT OF I	RESCISSION
other charge, and any security interest become after receipt of a notice of rescission, the crediproperty given as earnest money, down payr necessary or appropriate to reflect the terminal transaction. If the creditor has delivered any retain possession of it. Upon the performance the customer shall tender the property to the kind would be impracticable or inequitable, the Tender shall be made at the location of the proposition of the customer. If the creditor does no	to rescind, he/she is not liable for any finance or es void upon such a rescission. Within 10 days itor shall return to the customer any money or ment, or otherwise and shall take any action ation of any security interest created under the property to the customer, the customer may of the creditor's obligations under this section, creditor, except that if return of the property in he customer shall tender its reasonable value. perty or at the residence of the customer, at the of take possession of the property within 10 days of the property vests in the customer without
AUTHORIZATION TO D	DISBURSE LOAN FUNDS
since I/we have received the within Notice of not exercised my/our right to rescind.	rant that more than 3 business days has elapsed Rescission and that I/we (singly or jointly) have
Kristian Berrios Torres	WITNESS: Vavam. Manus By.
Marisabel Gonzalez-Borges	WITNESS:

Law Offices of

# LAURA M. MARINO, Esq.

Attorneys at Law
Website: www.lauramarinolaw.com
Telephone (413) 781-2557
Facsimile (413) 737-6616

Springfield: 15 Wilcox Street, Springfield, MA 01105 Northampton: 13 Old South Street, 2C Northampton, MA 01060

# **CERTIFICATE OF TITLE**

To: CITY OF SPRINGFIELD

Re: KRISTIAN BERRIOS TORRES AND MARISABEL GONZALEZ-BORGES ("Mortgagor(s)")

And to the MORTGAGOR(S)

I have examined the title to the premises described in a mortgage dated 2018 given KRISTIAN BERRIOS TORRES AND MARISABEL GONZALEZ-BORGES to you, in the records of the HAMPDEN County Registry of Deeds In Book 2210, Page of the Probate Court for the County of HAMPDEN, from 2011 1968 to the date of this Certificate,

and I hereby certify that at the time I recorded said mortgage the Mortgagor(s) held a good and sufficient record title to the mortgaged premises free from all encumbrances, excepting only matters which are expressly enumerated in Schedule "A" of this Certificate of Title, and I further certify that the Mortgagee holds a good and sufficient record first Mortgage to the property, subject only to such matters enumerated in Schedule "A".

I certify that I have given the Mortgagor(s) a Certificate of Title which complies with M.G.L. Chapter 93, Section 70.

As to the Mortgagor(s), the liability of the attorney rendering this certification is limited to the amount of the consideration shown on the deed, and as to the Mortgagee the liability of the attorney rendering this certification is limited to the original principal amount secured by the mortgage. This Certificate of Title is effective for the benefit of the Mortgagor(s) only so long as the Mortgagor(s) has/have title to the mortgaged premises and shall be effective for the benefit of the Mortgagee so long as the original debt secured by the mortgage remains unpaid.

I am informed by the Tax Collector of the town / city in which the premises are located that all taxes and other municipal assessments on or against said premises now due have been paid.

(The following clause to apply only in the case of a corporate mortgagor.)

I have examined the Articles of Organization, the by-laws and records of meeting of stockholders and directors of the Mortgagor and I am of the opinion that said mortgage and the note

accompanying it have been properly executed by the duly authorized officers of the Mortgagor and constitute valid corporate acts of the Mortgagor.

This Certificate of Title expressly **excludes any opinion** as the effect **on the title of** the following listed **exceptions**:

- 1. Any matter which does not appear in the records of said Registries.
  - 2. Any state of facts or error description which a recent accurate survey or personal inspection of the premises would disclose.
  - 3. Any existing Federal or **State** Laws, **Municipal Ordinances** or By-Laws which may affect **the use and** physical condition of the premises, including but not limited to existing zoning and subdivision control laws and regulations, State Sanitary Code, State Building Code and Lead Paint Law.

4. Any opinion as to the physical condition of said premises.

Date: 10/19/18

Attorney Laura M. Marino

Affected Premises: 58 Bancroft Street Springfield, MA

# **Quitclaim Deed**

KNOW ALL PERSONS BY THESE PRESENTS that We, Kristian Berrios Torres, an unmarried person of 58 Bancroft Street, Springfield, Massachusetts, Hampden County and Angel L. Valdes, a married person of 170 Arnold Street, Springfield, Massachusetts, Hampden County

FOR CONSIDERATION PAID AND IN FULL CONSIDERATION OF Less Than One Hundred Dollars and 00/100 (\$100.00)

Grant to Kristian Berrios Torres and Marisabel Gonzalez-Borges of 58 Bancroft Street, Springfield, Massachusetts, Hampden County as Joint Temants with Rights of Survivorshop With QUITCLAIM covenants

That certain piece and parcel of land located in the City of Springfield, County of Hampden and more particularly described as follows:

Bounded southerly by Bancroft Street Fifty (50) feet; Easterly by land now or formerly of the Heirs of Henry W. Barrett, and Amelia E. Barrett, about one hundred and seventy three (173) feet; Northerly by a passageway about fifty (50) feet, and Westerly by land now or formerly of George A. Williams about one hundred seventy three (173) feet.

Being lot #29 on plan of lots recorded in Book 216, Page 601.

Being the land with the buildings thereon located at 58 Bancroft Street, Springfield, Massachusetts.

As per M.G.L. c 188 s 13, the Grantor, under oath and subject to the pains and penalties of perjury, does hereby depose, state and certify that: (i) I release all rights of Homestead in the subject realty, (ii) that no spouse, no non-owner spouse, former spouse, or any other person resides in the home, and (iii) at the time of delivery of this deed, no spouse, former spouse, or any other person is entitled to claim the benefit of an existing estate of homestead.

MASSACHUSETTS STATE EXCISE TAX HAMPDEN COUNTY REGISTRY OF DEEDS

Ct1#: 37 Doc#: 63825 Fee: \$.00 Cons: \$.00 Being the same premises conveyed to Kristian Berrios Torres and Angel L. Valdes herein by deed of Juan C. Torres dated February 12, 2016 and recorded in the Hampden County Registry of Deeds in Book 21082, Page 349.

Executed as a sealed instrument this \_\_\_\_\_\_ day of September, 2018.

Commonwealth of Massachusetts

Hampden County

On this \_\_\_\_\_\_\_, 20\_\_\_\_\_\_, before me, the undersigned notary public Kristian Berrios Torres and Angel L. Valdes personally appeared, proved to me through satisfactory evidence of identification, which were

以るむ 'んし\_\_\_\_, to be the person whose name is signed on the preceding or attached document, and acknowledged to me that (he)(she)(they) signed it voluntarily for its stated purpose and swore of affirmed to me that the contents of the document are truthful and accurate to the best of his/her/they knowledge and belief.

LAURA M. MARINO Notary Public COMMONWEALTH OF MASSACHUSETTS My Commission Expires On May 18, 2025

**NOTARY PUBLIC** MY COMMISSION EXPIRES: 516/20

# The Commonwealth of Massachusetts

William Francis Galvin, Secretary of the Commonwealth

# Declaration of Homestead for Homes Owned

by Natural Persons (General Laws Chapter 188)

In situations where the home is owned by multiple owners, each owner may be best served to complete a separate declaration of homestead. I. MARISABEL GONZALEZ-BORGES (insert name of owner) □ We, \_ (insert name of owners) hereby declare homestead pursuant to M.G.L. c.188 and state that I/we own the home described below and occupy or intend to occupy the home as my/our principal residence. Owner Information 2. Check all that apply: ☐ I/we, \_\_\_\_\_ am elderly (62 years of age or older). (insert name (s)) ☐ I/we, \_ (insert name (s)) am/are disabled (have a physical or mental impairment that meets the disability requirements for Supplemental Security Income under 42 U.S.C. 1382c(a)(3)(A) and 42 U.S.C. 1382c(a)(3)(C). One of the following must be attached: 1) an original or certified copy of a disability award letter issued to the person by the United States Social Security Administration, or 2) a letter signed by a physician registered with the board of registration in medicine certifying that each person meets the disability requirements stated in 42 U.S.C. 1382c(a)(3)(A) and 42 U.S.C. 1382c(a)(3)(C). ☐ I am married to who is not a co-owner of the home but who occupies or intends to occupy the home as his/her principal residence. (insert name (s)) am/are servicemember(s) who may be subject to protection under the servicemember(s) Civil Relief Act, 50 U.S.C. App 533, should I/we be called to active duty. Home Information 58 BANCROFT STREET, SPRINGFIELD \_\_\_\_\_, Massachusetts. 3. Address: (street number and name, city/town) ONE of the following: 4. Select₄ Registry of Deeds Cooled hore 1th HAMPDEN COUNTY Deed is recorded in \_ (district/county) Certificate of Title \_\_ registered in the Land Registration Office\_ (number) (book) (page) , Docket number Inheritance from \_ (name of previous owner) \_\_\_\_\_ in \_\_\_\_ (number) (county)

(number)

For manufactured homes, license number \_

To be signed by Applicant(s) in front of Notary Public. Signed under pains and penalties of perjury this For Use by Notary Public Only: COMMONWEALTH OF MASSACHUSETTS before me, the undersigned notary public, personally appeared proved to me through satisfactory evidence of identification, which were to be the person(s) who signed the preceding or attached document in my presence, and who swore or affirmed to me that the contents of the document are truthful and accurate to the hest of (his) (her) (their) knowledge and belief. Notary Publica My commission expires: LAURA M. MARINO Notary Public COMMONWEALTH OF MASSACHUSETTS My Commission Expires On

May 18, 2025

5. I/we, whose names are signed on this document, acknowledge that I/we sign it voluntarily for its stated purpose.



# City of Springfield Office of Disaster Recovery and Compliance

# CDBG National Disaster Resilience Program Awarding Federal Agency: United States Department of Housing and Urban Development Federal Award Number: B-13-MS-25-0002

# SUBROGATION AND ASSIGNMENT AGREEMENT

This Subrogation and Assignment Agreement ("Agreement") is made and entered into on this  $\int_{-\infty}^{5+}$  day of November, 2018, by and between Kristian Berrios Torres and Marisabel Gonzalez-Borges ("Subrecipient") and the City of Springfield.

- Assignment Relating to Funds Received under CDBG-Disaster Recovery Program 1. In consideration of Subrecipient's receipt of funds under the CDBG National Disaster Resilience (CDBG-NDR) Program administered by the City of Springfield, Subrecipient hereby assigns to the City of Springfield all of Subrecipient's future rights to reimbursement and all payments received under any policy of casualty or property damage insurance (the "Policies") or under any reimbursement or relief program related to or administered by the Federal Emergency Management Agency ("FEMA") or the Small Business Administration ("SBA") for physical damage to the Structure (defined below) that was the basis of the calculation of Subrecipient's award to the extent of the Note or Loan proceeds paid to Subrecipient under the Program. The proceeds or payments referred to in the preceding sentence, whether they be from insurance, FEMA or the SBA, shall be referred to herein as "Proceeds." The rights Subrecipient assigns are specific to the structure with respect to which Note or Loan proceeds were paid (the "Structure") which is described in Subrecipient's application with the Program, and include proceeds arising out of physical damage to the Structure originally caused by the June 2011 Tornado but also including Proceeds received for damage to the Structure caused by any subsequent event that occurred until the commencement of repair or reconstruction utilizing Program funds. The Policies include, but are not limited to, policies characterized as wind, flood or any other type of casualty or property damage insurance coverage held by Subrecipient and which provides coverage for physical damage to the Structure.
- 2. <u>Cooperation and Further Documentation</u> Subrecipient agrees to assist and cooperate with the City of Springfield should the City of Springfield elect to pursue any of the claims Subrecipient has against the insurers for reimbursement under any such policies. Subrecipient's assistance and cooperation shall include allowing suit to be brought in Subrecipient's name(s), giving depositions, providing documents, producing records and other evidence, testifying at trial and any other form of assistance and cooperation reasonably requested by the City of Springfield. Subrecipient further agrees to assist and cooperate in the attainment and collection of any Proceeds that the Subrecipient would be entitled to under any applicable FEMA or SBA program as described above. If requested by the City of Springfield, Subrecipient agrees to execute such

further and additional documents and instruments as may be requested to further and better assign to the City of Springfield, to the extent of the Note or Loan proceeds paid to Subrecipient under the Program, the Policies, the disaster relief funds from FEMA or SBA and/or any rights thereunder, and to take, or cause to be taken, all actions and to do, or cause to be done, all things requested by the City of Springfield to consummate and make effective the purposes of this Agreement.

- 3. <u>Authorization for City of Springfield to Contact Third Parties</u> Subrecipient explicitly allows the City of Springfield to request of any company with which Subrecipient held Policies or FEMA or the SBA any non-public or confidential information needed by the City of Springfield to monitor/enforce its interest in the rights assigned to it under this Agreement and to give Subrecipient's consent to such company to release said information to the City of Springfield.
- 4. Agreement to Turn over Proceeds; Future Reassignment If Subrecipient (or any entity holding a lien on the Structure, except to the extent required by superior loan documents) hereafter receives any insurance payment or disaster relief or reimbursement funds for physical damage to the Structure (not including proceeds received to cover contents), Subrecipient agrees to promptly pay such amounts to the City of Springfield if Subrecipient received grant proceeds under the Program in an amount greater than the amount Subrecipient would have received if such insurance and\or disaster relief or reimbursement payment had been considered in the calculation of Subrecipient's award. Once the City of Springfield has recovered an amount equal to the grant proceeds paid to Subrecipient, the City of Springfield will reassign to Subrecipient any rights assigned to the City of Springfield pursuant to this Agreement.
- **5.** <u>Mortgage City of Springfield Rights</u> Subrecipient acknowledges that this Agreement does not impair Subrecipient's mortgage or City of Springfield's rights as loss-payee under any deed of trust or mortgage on the Structure.

# 6. <u>Miscellaneous</u>

- (a) WARNING: Subrecipient is hereby notified that intentionally or knowingly making a materially false or misleading written statement to obtain property or credit, including a mortgage loan, is a violation of Massachusetts General Law Part IV Title I Chapter 266 Section 67b, and, depending, is punishable by imprisonment for up to five years and/or a fine not to exceed \$10,000.00.
- (b) Subrecipient hereby represents that he\she has received, read, and understand this notice of penalties for making a materially false or misleading written statement to obtain a home loan.

- Subrecipient represents that all statements and representations made by Subrecipient regarding Proceeds received by Borrower shall be true and correct as of the date of Closing.
- In any proceeding to enforce this Agreement, the City of Springfield shall be entitled to recover all costs of enforcement, including actual attorney's fees.

day of November, 2018. **EXECUTED** this

# SUBRECIPIENT:

Kristian Berrios Torres

EXECUTED this Stay of Nov., 2018.

CITY OF SPRINGFIELD:

Name: Geraldine McCafferty
Title: Director of Horsing

# CITY OF SPRINGFIELD OFFICE OF HOUSING 1600 EAST COLUMBUS AVE SPRINGFIELD, MA 01105

# **Bid Proposal Form**

To:	Kristian Torres	Date Submitted: 6.14.18
		Property Address: 58 Bancroft Street 01107
	all Work shown and/or specified in	ed as per your request dated June 1, 2018. This bid the bid documents received for this job, which are:
	1. General Conditions	Pages, Dated
	2. Work Write-Up	Pages, Dated
	3. Code Violation Notice	Pages, Dated
	4. Performance Manual	Pages, Dated
	5. Addenda 1 to	Pages, Dated
	6. Other heat Paint	

The undersigned, having become thoroughly familiar with the terms and conditions of the proposed Contract Documents and with local conditions affecting the performance and costs of the Work at the place where the Work is to be completed, and having fully inspection the site in all particulars, hereby proposes and agrees to fully perform the Work within the time stated and in strict accordance with the proposed Contract Document including furnishing of any and all labor and materials, and to do all work required to construct and complete said Work in accordance with the Contract Documents, for the total sum of money.

#### Base Bid:

All labor, materials, services, and equipment necessary for the completion of the Work:

Severy + housen Winshvadre Dollars (\$ 7096500)

and Sixty Five doblers

# ADDITIONAL SUBMISSIONS

If awarded the Contract, the Bidder agrees to present the following documents to the Owner prior to the issuance of the Notice to Proceed: valid certificates covering Property Damage, Liability, and Workers' Compensation Insurance, all necessary building permits, and a Sworn Statement for Contractor and Subcontractor to Owner listing all of the subcontractors and subcontract amounts.

# **RETAINAGE**

It is further agreed that if awarded this contract, 10% of all requested payouts will be retained until the project is completed to the approval of the Owner and all approving agents. Completion of this project will require 60 calendar days. This proposal is valid for a period of 60 days.

# TIME

Upon request by Our Program, contractor agrees to itemize any/or all aspects of this proposal on the attached form.

# **ALTERNATE ITEMS TO BID**

NOTE: Failure to submit line prices for each individual alternate item may exclude your entire bid proposal.

<u>Item Number</u>	Line Price
1)	\$
2)	\$
3)	\$
4)	\$
5)	\$
6)	\$
TOTAL	\$

ADDITIONAL COMMENTS, RECOMMENDATIONS, SUBSTITUTIONS, ETC.:

#*************************************	***************************************
•	
THE CONTRACTOR FURTHER PROPOSES THE FOLDELETIONS OR ADDITIONS TO THE WRITE-UP:	LOWING CHANGES,
	<u>PRICE</u>
	\$
	\$
	\$
	V
Contractor:	Simoton
Address:	Signature
Phone:	TD':4
	Title
By my signature as a Contractor or agent of the Coninspected the above noted property and have received Invitation to Bid and/or Bid Form.	ntractor, I swear that I have fully and all documents as listed on the
Signature	
Title OWAZ-	
Company Aldred Shettelror Cc	
Date 6/14/14	

## SPECS BY LOCATION/TRADE

3/9/2018

Pre-B	id Site Visit:	· Case Number:				
Bidding	Open Date:	Droingt Manager				
Bidding	Close Date:				·······	
	Initial:					
Address: 58 1	Bancroft Street	Unit: U	nit 01			
Location:	1 - General Requirements	Aoprox Wa	all/SF: 0		Ceiling/Floor S	F: 0
Spec#	Spec		Quantity	Units	Unit Price	Total Price
Trade: 1	General Requirements					****
the "Date in the work do	OWNER ACCEPTS SCOPE OF Notice of applicant(s) certifies that help inspected date of & reference accepted & has initialed & dated each accepted by the following the follo	she has particlpated in the deverred to as Exhibit 1. After care	1.00 Velopment o eful review	DU of this W the appli	ork.Write Up (\ cant understan	WWU) with ds & accepts
Applicant	t Date Applicant Da	ate				
Write Up (\	CONTRACTOR ACCEPTS SCO signed contractor certifies that he/sl WWU) with the "Date Inspected" dapage of the WWU.	he has carefully reviewed & ac	1.00 grees to per to as Exhil	form the	work describe contractor sha	d in this Work all initial &
xContract	or Date					
<b>24</b> Alt materia preparation	MANUFACTURER'S SPECS PR ils shall be installed in full accordance n, methods, protection and testing.		1.00 ecifications		ng conditions,	surface
http://www	VENTILATION—ASHRAE 62.2-0 ing unit must have a ventilation syst ashrae.org/technology/page/548 are buildingscience.com/documents/re	em that meets ASHRAE 62.2			nnologies/	
30	WALL NAMING PROTOCOLS		1.00		Ü	
Walls and	attached components shall be iden as elevation or the "street side" of the	tified with the letters A, B, C & e house. Moving clockwise, t	D. Wall A	is alwavs	the wall that is C, D.	s closest to
The last is	components, for example, a window window D4 moving in a clockwise outper, lower. For example: Replace	direction. These locational ma	arkers may	also be d	would window icombined with	is Window D1. the adjectives:
31	CONSTRUCTION DEFINITIONS	3	1.00	GR		
material, p	eans to purchase, set up, test and vourchase new material, deliver, insta through replacement, adjustment ar art.	all, test and warrant. "Repair" r	neans to re	turn a bi	ilidina compon	ent to like new
32	SUBSTITUTION APPROVAL PI	ROCESS	1.00	GR		
manufactu	ests for substitutions of specified pro urer's specifications; full installation at contract award.	oprietary items must accompai instructions and warranties. Ti	nv the initial	proposa	al and shall inc or will notify the	lude: the e contractor of
34	LINE ITEM BREAKDOWN		1.00	DU		
	rent winning bidders shall provide th	ne owner with a line item cost t			working days o	of a request.
35	VERIFY QUANTITIES/MEASUR		1.00		•	-
All Quanti (RM) or D	ties stated in the attached specifical welling Unit (DU) (e.g. SF of Drywa latory site inspection prior to bid sub	tions for this address using Ur II) are for the contractor's conv	nits of Meas renience ar	ure othe	e verified by the	ne contractor

Unit: 1	Jnit 01			KBT 3÷9-1
Approx V	/all-SF: 0	(	Deiling/Floor S	F. O. Property
	Quantity	Units	Unit Price	Total Price
tities found by to a bid. Claims fo omission.	he contractor or additional	r must be funds du	e communicate e to discrepan	ed to the cies in
	1.00	AL		
opies of the folio	owing indicat Lead Ab	ed permi atement;	ts to the agend	cy: tos
	1.00	DU		
oid is presumption of the local juris	ve evidence		oldder has tho	roughly
	1.00	GR		
g hours betwee ours must be ap	n 8:00am an proved by th	d 6:00pn ie homed	n Monday thro owner.	ugh Friday.
	1.00	GR		
to be new, of fir clalist.	st quality and	d without	defects - unle	ss stated
d skilled in their I to eliminate da	1.00 particular tra image.	GR ade as w	ell as the tasks	assigned to
ampden, and the	e State of Ma	GR and comp assachus	ply with all gov setts pertaining	reming codes g to building
	1.00	GR		
hina & flashina :	prior to instal	llation of	new felt & chir	hae selna
	1.00	DU		
t. Further, conti	ractor shall fi	umish ow	mer with all ma	anufacturore!
****	<b>*</b>			
red when more to nporarily humar airs, painting, te s, and the estab int hazard reduce	than; n exposure o emporary cor lishment and ction activity	r likely ex tainmen l operatio takes pla	oposure to lead t, specialized on on of managen ce. There may	d-based paint cleaning, nent and y be more
	Approx Manuscription Approx Manuscription Approx Manuscription Approx Manuscription Approx Manuscription Approximate Approxima	tities found by the contractor a bid. Claims for additional omission.  1.00  pies of the following indicate Zoning; Lead Ab  1.00  oid is presumptive evidence of the local jurisdiction.  1.00  g hours between 8:00am and ours must be approved by the solution of the local jurisdiction.  1.00  d skilled in their particular trail to eliminate damage.  1.00  or shall facilitate inspection and the State of Management and worker safety.  1.00  aled from view before it is cleaning & flashing prior to instant and the state of the prior to reserve the prior to the prior to reserve the prior to reserve the prior to the prio	Quantity Units    Quantity Units	Approx Wall SF 0. Ceiling/Floor.S  Quantity Units Unit Price  titles found by the contractor must be communicate a bid. Claims for additional funds due to discrepant omission.  1.00 AL

Address: 58	Bancroft Street	Unit: Unit 01			VAT a 20
Location:	1 - General Requirements	Approx Wall SF: 0	(	Seiling/Floor S	<u>¥8T⊰9-18</u> F 0
Spec #	Spec	Quantity	diginal places	Unit Price	Total Price
Trade: 9	Environmental Rehab				
environme	g unit or work site. The clearance process includes a ntal samples. Dust-lead standards for clearance are fi R Part 35 - Subpart B - Section 35.110 Definitions, for	ound at Sec. 35.1320.	collection	n and analysis	of
9003	LEAD-SPECIFIC LAWS, RULES, REGULATIONS GUIDELINES	<b>&amp;</b> 1.00	GR	<del>1"</del>	•
lead dust e Hazard Co	tion of this work shall comply with all applicable federa environments, including but not limited to: 29 CFR 192 emmunication Standard; 40 CFR Part 745 - Lead-Base (EPA Regulations); 24 CFR Part 35 - HUD's Lead Sa	:6.62 - Lead Constructi ed Paint Poisoning Prev	on Stand	ard: 29 CFR10	210 1200
		l	_ocatio	n Total:	
Location:	2 - Exterior	Approx: Wall SF: 0		Ceiling/Floor S	F 0
Spec #	Spec	Quantity	Units	Unit Price	Total Price
Trade: 7	Masonry				· · · · · · · · · · · · · · · · · · ·
using porti	MASONRY—REPOINT ortar at least 1/2". Remove all loose material with cleat and cement mortar. Reinstall flashing, tool concave jo	100.00 ar water. Saturate joints bints and clean brick fac	SF with wat	er and repoint	800 in 1/2" lifts
Repair all	loose mortar joints on foundation walls.				5
<b>1235</b> Remove d	BRICK WALL REPAIR amaged brick and tooth replacement brick into wall.	40.00 Watch brick and tooling	SF as closel	y as possible.	[200
REAR RIG	GHT CORNER OF FOUNDATION AND REAR BULKI	EAD INTERIOR FOUN	DATION	WALLS.	
Color of bi	MASONRY CHIMNEYREBUILD  In chimney to below lowest point on roof. Rebuild chim  rick to match existing as closely as possible. Chimney  himney cap and terra cotta flue liner.	5.00 ney using new 4" thick y to a height required by	LF solid bric the state	ks without core building code	2300 ed holes. e. Install roof
Trade: 10	Carpentry				
and windo barrier and	SIDING—VINYL side of house of all damaged vinyl siding. Install new w trim after replacing all deteriorated exterior building d siding color to match existing as close as possible,	components. Wrap ho exposure and texture w	me with t ith 50 ye:	tyvek vapor/ in ar warranty.	filtration
REPLACE INSTALL	EALL SIDING ON RIGHT SIDE OF HOUSE AND DO ALUMINUM COIL ON WINDOW TRIM WHERE MISS	GHOUSE ENTRANCE I BING.	LEADING	S INTO BASEI	MENT.
<b>3575</b> Replace d	PORCH REPAIR—CUSTOM lamage section plywood flooring on 2nd floor porch.	1.00 Install exterior grade ply	EA wood to	replace damag	300 ged section.
stepping s	STEPSREPL EXTERIOR  f existing steps. Construct a replacement unit with two stock treads, on a solid concrete footer. Frame stairs drail with balusters on both side 32" above tread nosin	4' wide connecting to fro	ont and re	aar enfrances	2000 4" PTP Construct a
Two sets		g. v.a tamig mac s.	o graopa	oic.	
Trade: 15	Roofing				
membrane	EPDMFULLY ADHERED  oose materials off of roof. Install manufacturers appre with adhesive per manufacturer's specs. All membre stallation procedure to follow manufacturer's specs. Fi	ane flashing, metal flast	ninge and	i countar flach	00000 00

	n Estados	ASSESSMENT			KRI 3-9-18
ocation:	2-Exterior	Approx. Wall SF 0	description for the second of	Ceiling/Floor S	
Spec #	Spec	Quantity	Units	Unit Price	Total Price
rade: 15	Roofing		<del></del>		
	roof at rear of house,				15000
the eaves self-sealin Install step	REROOF—1/2" DECK/FIBERGLASS SHINGLE oof to deck. Install 1/2" CDX plywood over entire roo and in the valleys. Install 15 lb. felt as underlayment g, 35 year warranty fiberglass/ asphalt strip shingles of flashing at all wall junctures. Color choice by owner S FRONT PORCHES AND ALL SIDE ROOFS.	t on the remainder of the .   Replace all flashing, in	decking.	Install Owens	s Corning
					16
<b>4635</b> Dispose o owner.	GUTTER-5" SEAMLESS ALUMINUM of gutter. Install 5", K- type, seamless, .027 gauge alu	140.00 uminum gutter to service		hite or brown o	color choice by
Along peri	imeter of house and porches				
<b>4640</b> Dispose o center.	DOWNSPOUT5" SEAMLESS ALUMINUM of existing downspout. Install 5", square, seamless, .	140.00 027 gauge, white, alumir		nspout, Strap	1000 at least 3' on
			Locatio	n Total:	
ocation:	-3 · Basement	Approx Wall SF: 0		Geiling/Floor S	SE 0
Spec #	Spec	Quantity	Units	·Unit Price	Total Price
rade: 7					
.444.	Masonry				
1235 Remove of tooling as	Masonry  BRICK WALL REPAIR  damaged brick in chimney chase behind hot water ta closely as possible.  chase in basement has missing brick.	5.00	SF		350
1235 Remove of tooling as Chimney	BRICK WALL REPAIR damaged brick in chimney chase behind hot water ta closely as possible. chase in basement has missing brick.	5.00	SF		350
1235 Remove of tooling as Chimney  Frade: 21 6245 Dispose of piping & bothermoste	BRICK WALL REPAIR damaged brick in chimney chase behind hot water ta closely as possible. chase in basement has missing brick.	5.00 snk and tooth replacemer  1.00 se & install a gas fired, ca ation includes all power &	SF at brick in EA st iron, ja	acketed boiler,	350 brick and 7400 distribution
1235 Remove of tooling as Chimney  Trade: 21 6245 Dispose of piping & bettermoster indoor ter	BRICK WALL REPAIR damaged brick in chimney chase behind hot water ta s closely as possible. chase in basement has missing brick.  HVAC  BOILER—GAS REPLACE—COMPLETE of heating equip. & radiators to code legal landfill. Siz baseboard convectors to service entire house. Install at, expansion tank, one circulation pump, water & ga	5.00 sink and tooth replacement  1.00 se & install a gas fired, ca ation includes all power 8 s supply & flue piping. Ins AFUE rating 86.	SF at brick in EA st iron, ja & control stallation	acketed boiler, wiring, a set b required to ma	350 brick and 7400 distribution
1235 Remove of tooling as Chimney  Trade: 21 6245 Dispose of piping & be thermoster indoor ter	BRICK WALL REPAIR damaged brick in chimney chase behind hot water ta s closely as possible. chase in basement has missing brick.  HVAC  BOILER—GAS REPLACE—COMPLETE of heating equip. & radiators to code legal landfill. Size baseboard convectors to service entire house. Installed, expansion tank, one circulation pump, water & gamperature when outdoor temperature is -10 F. Min. As a several rooms missing baseboard heaters and piping	5.00 sink and tooth replacement  1.00 se & install a gas fired, ca ation includes all power 8 s supply & flue piping. Ins AFUE rating 86.	SF at brick in EA st iron, ja & control stallation	acketed boiler, wiring, a set b required to ma	350 brick and 7400 distribution
1235 Remove of tooling as Chimney  Frade: 21 6245 Dispose of piping & better mostal indoor termostal indoor	BRICK WALL REPAIR damaged brick in chimney chase behind hot water ta s closely as possible. chase in basement has missing brick.  HVAC  BOILER—GAS REPLACE—COMPLETE of heating equip. & radiators to code legal landfill. Size baseboard convectors to service entire house. Installed, expansion tank, one circulation pump, water & gamperature when outdoor temperature is -10 F. Min. As a several rooms missing baseboard heaters and piping	5.00 ank and tooth replacement  1.00 as & install a gas fired, ca ation includes all power & as supply & flue piping. Ins AFUE rating 86. ag. Make sure all rooms  TED 1.00 ag. power vented, insulate are relief valve, discharge arior. Provide separate ele ar. If the water heater is le ocated on an upper floor	SF at brick in  EA st iron, jak control stallation have fur  EA d to minical tube to	acketed boiler, wiring, a set b required to material heat.	350 a brick and  7400 distribution ack aintain 70F.  2000 as fired water or, condensate gas piping with a floor
1235 Remove of tooling as Chimney  Frade: 21 6245 Dispose of piping & better mostal indoor termostal indoor	BRICK WALL REPAIR damaged brick in chimney chase behind hot water tall closely as possible. chase in basement has missing brick.  HVAC  BOILER—GAS REPLACE—COMPLETE of heating equip. & radiators to code legal landfill. Size baseboard convectors to service entire house. Installed, expansion tank, one circulation pump, water & gamperature when outdoor temperature is -10 F. Min. As several rooms missing baseboard heaters and piplic expansion, glass lined, minimum .67 energy factor (EF than 6 year warranty. Include pressure and temperature's manual and all duct work to power vent to extend the control of the control of the control of the drain. If it is a drained to the exterior. Recycle the existing water in drained to the exterior. Recycle the existing water in drained to the exterior. Recycle the existing water in drained to the exterior.	5.00 ank and tooth replacement  1.00 as & install a gas fired, ca ation includes all power & as supply & flue piping. Ins AFUE rating 86. ag. Make sure all rooms  TED 1.00 ag. power vented, insulate are relief valve, discharge arior. Provide separate ele ar. If the water heater is le ocated on an upper floor	SF at brick in  EA st iron, jak control stallation have fur  EA d to minical tube to	acketed boiler, wiring, a set b required to material heat.	350 a brick and  7400 distribution ack aintain 70F.  2000 as fired water or, condensate gas piping with a floor

Page 4 of 10

Address:	58 1	Bancroft Street	J.	Init: Unit 01			
Location		3 - Basement		onit: Unit Unit		del ambalanta del marco de la companya de la compa	BT 34-18
Spec	S. S	Spec	Abt			Celling/Floor S	Single Land Control of the Control o
Trade:	23	Electric		Quantity	Units	Unit Price	Total Price
		rect all unauthorized, unappro	oved or defective wiring so a	s to comply to Flori	rical Cor	<u> </u>	
		TOR TO TEST AND CHECK					•
OPEF	RATIC	N.			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	OTT NOT E	•
				L	.ocatior	n Total:	
Location	1	4 - Kitchen	Aor	orox Wall SF: 350		 Deiling/Floor S	
Spec		Spec		Quantity	Units	Unit Price	Total Price
Trade:	10	Carpentry		- Cauring		Omerrice	Total Frice
3315		TRIMDOOR SET 1"X4"		1.00	EA		200
Trim I	both s	ides of interior door, including	g header, stops and casings.	. Use 1"x4", #2 gra	دے de pine d	or better.	
		ading from kitchen to dining r			-		
3705		CABINETS-REPAIR		6.00	LF		500
Repa Secu	ir bas relv re	e and hanging cabinets by re- fasten loose hardware. Clea	hanging plumb and level and	replacing missing	hardwar	e, doors and d	rawers.
		2" base cabinet is not attache	•		RE LOC	SF	
Cust		BOX IN PIPING		1.00		, G <u>C</u> .	400
Instal	ll woo	d encasement around basebo	pard heating pipes in comer	near doorway.  Enc	AL asement	can be 1 by p	ine or
piywo	oa.						
Trade:	20	Floor Coverings					
5930 Instal		UNDERLAYMENT AND VI	NYL SHEET GOODS	130.00	SF	Indiana.	2100
on ce	aner a	underlayment grade plywood allowing a 1/4" gap at wall. Fi	il seams with a manufacturei	r approved filler In	stall 070°	thick backed	vinul chaof
good	sw n	ninimum seams, per manufac I color.	t. recommendations. Install	metal edge strips in	n openin	gs. Owner's o	choice of
Trade:	23	Electric					
					<b></b>		5
<b>7560</b> Repa		RECEPTACLE REPAIR se receptacle outlet behind re	frigerator. needs to be re se	1.00 scured into wall	EA		200
		·	•				
	·············			ı	.ocatio	n Total:	
Location	1	5 - 1st floor Bathroom	Apj	orox Wall SF 210		Ceiling/Floor S	F. 56
Spec	:#	Spec		Quantity	Units	Unit Price	Total Price
Trade:	20	Floor Coverings			·		•
5930		UNDERLAYMENT AND VI	NYL SHEET GOODS	50.00	SF		700
Instal on ce	ll 1/4" enter a	underlayment grade plywood allowing a 1/4" gap at wall. Fi	using 7d screw shank or ce	ment coated nails,	or narrov	v crown coated	l staples, 6"
good	S W/	anunum seams, per manurac	t. recommendations. Install	metal edge strips i	n openin	tnick, backed gs. Owner's d	vinyi sneet hoice of
раце	m an	1 COIOF.					
Trade:	22	Plumbing					8-
6900 Rese		VANITY-RESECURE the loose 24" vanity cabinet to	wall. Seal all nanotration #	1.00	EA	object for the	<u>400</u>
conn	ection	s using expanding foam or ca	aulk and cover with chrome e	eschucion plates.	uis and c	aoinet for plur	noing · / o
randyranam militär Milia		established business page 186 feet to be a control of the control					430

Address.	58 1	Bancroft Street		Unit: I	Unit 01			
Location		5 - 1st floor Bathroor	n		Ialise: 210		Ceiling/Floor S	<u> </u>
Spec	#	Spec			Quantity		Unit Price	
Trade:	22	Plumbing		<u> </u>	quantity	Onics	Omt Price	Total Price
6965	········	<u> </u>				· · · · · · · · · · · · · · · · · · ·	<u> </u>	
	cure s ower (	SHOWERSTALLRES hower stall glass walls an walls.	d door to base of sho	ower, remove all d	1.00 lefective cau	AL Ilking an	d reseal all sea	ams and joints
7004 Reset	exist	TOILET-RESET ing toilet on new wax ring	with polyethylene fla	nge. Install brass	1.00 bolts and nu	EA end sa	ecure fightly to	100
Frade:	23	Electric		_			codic agilay to	the moor.
fixture fan su http:// galval a met ductw	e musi uch as www. nized al hoc ork w	FAN/LIGHT FIXTURE-ENERGY STAR approved of accommodate 2 - GU24 of the EFI Fan/Light Time Denergyfederation.org/consental duct the same diamoded vent of like diameter ith vinyl or foil faced R 8 rembly to the ceiling with	ceiling mounted Fan/ M operating at 1 Sor fluorescent lamps. Delay Switch part # 5 sumer/default.php/cPneter as the fan outle and with damper. A minimum duct insulate	ne or less, with an Switch fan & light 100.505 (in Ivory) Path/39_766_134 ( It and vent to the e	integral dan using a sing or equipped exterior ideal	nper, and the switch with a hu by throug	d vented to the n with a time de umidistat senso th a wall or gab	exterior. The elay for the or. Install ole end using
	Mark Sanda			i ja variantiin kan kan kan kan kan kan kan kan kan ka	i Omborio ama a mana na mana a ma		n Total:	3>5
ocation	402705023FE	6 - Living Room		Approx. VA	/all SF、336		Ceiling/Floor S	F 144
Spec		Spec			Quantity	Units	Unit Price	<b>Total Price</b>
rade:	20	Floor Coverings	¥					
		VINYL COMPOSITION isting VCT tile flooring. Li cturer's recommendation around perimeter. Owner's	ay 12"x12"x1/8" vinyl s. Square to room ax	is ancient mercie	144.00 color group edge strips a	SF B as mad it openin	de by Armstror gs,and shoe m	g or Azrock, polding or 4"
rade:	23	Electric	····					
1101111	10tain	INSTALL RECEPTACL ory, duplex, 15 amp recept c (NM) cable. Fish wire a DDITIONAL OUTLET ON	otacle and ivory cove nd repair all tear out.		1.00 above floor	EA level usi	ing copper 12-	350
					I	_ocatio	n Total:	
_ocation		7-Dining Room		Approx W	all SF 329	VASSASSILING SANSAS	Ceiling/Floor S	F: 131
Spec	#	Spec			Quantity	Units	Unit Price	Total Price
Trade:	17	Drywall & Plaster	· -					
<b>5270</b> Apply white.	tape a	DRYWALL-FINISH and 3 coats of compound	feathered out at leas	at 8". Wet sand re	130.00 ady for pain	SF t. Seal d	lrywall, prime a	1000 and paint flat
Frade:	20	Floor Coverings						
<b>5920</b> Repail nails, ( 12"x12	r all da or nar 2"x1/8	UNDERLAY AND VINYI amage subflooring prior to row crown staples, 6" on " vinyl composition tile, co	Installing 1/4" under	rlayment grade ply	135.00 Wood using seams with a	SF 7d screv a manufac	w shank or cen	nent coated ed filler. Lay

	Bancroft Street Unit Hait 04	The same		The second secon	TANK TANKS OF A SECURE AND A SECURE ASSESSMENT OF THE SECURE ASSESSMENT
ocation:	Bancroft Street Unit: Unit: 01  7 - Dining Room Approx: Wall SF	200		NAMED OF STREET PROPERTY OF STREET	<u> 467 892</u>
Spec #	Spec Quant	######################################	antantess	Ceiling/Floor S	
rade: 20	Floor Coverings	ity (	Units	Unit Price	Total Price
Square to	room axis. Include metal edge strips at openings,and shoe molding or 4" n-stock color.	vinyl b	ase ar	ound perimete	er.Owner's
		Lo	cation	Total:	
ocation:	8 - Master Bedroom Approx: Wall SF: 4	413	(	Deiling/Floor S	F 207
Spec#	Spec Quant	ity l	Jnits	Unit Price	Total Price
Frade: 10	Carpentry				
<b>3260</b> Rehang do Repair loos	REWORK INTERIOR DOOR  1.  DOOR. Adjust door and lockset to operate properly. If door rubs floor or carp se door knob.	.00 peting,	EA , trim bo	ottom of door	200 to clear.
shelf, 1-3/8	a 28" deep by 7' wide closet in bedroom along wall. Hang, tape and 3 coa ning. Hang a 3'x 6'8" louvered pine bifold door including overhead track a B" hanger rod and 1"x 4" interior base. Match exterior base to room. Prim	at finis			h sides of the 12" plywood
	e in ceiling at closet area.				
Frade: 20	Floor Coverings				
5972	CARPET (CUT PILE) & PAD-GREEN LABEL 23.	00	SY		1100
Install FHA minimum c certification edge strips	A approved, Nylon/Olefin blend cut pile weave carpet. Install over a 1/2" mof seams in both pad and carpet. Carpet and Pad must meet the Carpet and Stretch carpet to eliminate puckers, scallops & ripples. Include premiur at transition to resilient, tile or wood floors. New carpet to be seamed to ling closets. Owner's choice of color and style.	nediun	n densi ug Insti	tute's Green L	.abel
Install FHA minimum c certification edge strips	A approved, Nylon/Olefin blend cut pile weave carpet. Install over a 1/2" not seams in both pad and carpet. Carpet and Pad must meet the Carpet and Stretch carpet to eliminate puckers, scallops & ripples. Include premiurs at transition to resilient, tile or wood floors. New carpet to be seamed to	nediun	n densi ug Insti	tute's Green L	with a abel
Install FHA minimum of certification edge strips floor includ  Frade: 23  8017  Remove th B552QI-W P2620-30E	A approved, Nylon/Olefin blend cut pile weave carpet. Install over a 1/2" mof seams in both pad and carpet. Carpet and Pad must meet the Carpet and Stretch carpet to eliminate puckers, scallops & ripples. Include premiur at transition to resilient, tile or wood floors. New carpet to be seamed to ling closets. Owner's choice of color and style.  Electric	nediurand Rin sea carpe	n densi ug Insti m tape et in adj EA h white	tute's Green L , tackless strip oining rooms.  ceiling fan Mo	with a abel os & metal Cover entire
Install FHA minimum of certification edge strips floor includ  Frade: 23  8017  Remove th B552QI-W P2620-30E	A approved, Nylon/Olefin blend cut pile weave carpet. Install over a 1/2" mof seams in both pad and carpet. Carpet and Pad must meet the Carpet and Stretch carpet to eliminate puckers, scallops & ripples. Include premiur at transition to resilient, tile or wood floors. New carpet to be seamed to ling closets. Owner's choice of color and style.  Electric  ENERGY STAR CEILING FAN LIGHT FIXTURE  1. The existing ceiling fan. Install an ENERGY STAR® approved Farmington of the At Home Depot with a ENERGY STAR® approved Progress Lighting At EBWB at Home Depot switched at the room entrance by a Leviton Do if Reference in the state of the stat	nediur and Ri n sea carpe 00 52 inc ir Pro est Fa	n densi ug Insti m tape et in adj EA h white light fix in and I	tute's Green L , tackless strip oining rooms.  ceiling fan Mo	with a abel os & metal Cover entire
Install FHA minimum of certification edge strips floor includ  Frade: 23  8017  Remove th B552QI-W P2620-30E separate st	A approved, Nylon/Olefin blend cut pile weave carpet. Install over a 1/2" mof seams in both pad and carpet. Carpet and Pad must meet the Carpet and Stretch carpet to eliminate puckers, scallops & ripples. Include premiur at transition to resilient, tile or wood floors. New carpet to be seamed to ling closets. Owner's choice of color and style.  Electric  ENERGY STAR CEILING FAN LIGHT FIXTURE  1. The existing ceiling fan. Install an ENERGY STAR® approved Farmington STAR H at Home Depot with a ENERGY STAR® approved Progress Lighting Aid EBWB at Home Depot switched at the room entrance by a Leviton Do it Be witching for the fan and light.	nediurand Rim sea carpe  00 52 incir Projest Fa	n densi ug Insti m tape et in adj EA h white light fix in and I	tute's Green L , tackless strip oining rooms.  ceiling fan Me ture Model # Light Control w	with a abel os & metal Cover entire
Install FHA minimum of certification edge strips floor includ frade: 23  8017 Remove th B552QI-W P2620-30E separate st	A approved, Nylon/Olefin blend cut pile weave carpet. Install over a 1/2" mof seams in both pad and carpet. Carpet and Pad must meet the Carpet and Stretch carpet to eliminate puckers, scallops & ripples. Include premiur at transition to resilient, tile or wood floors. New carpet to be seamed to ling closets. Owner's choice of color and style.  Electric  ENERGY STAR CEILING FAN LIGHT FIXTURE  1. The existing ceiling fan. Install an ENERGY STAR® approved Farmington State Home Depot with a ENERGY STAR® approved Progress Lighting Aid EBWB at Home Depot switched at the room entrance by a Leviton Do it Be witching for the fan and light.  9-Front Bedroom  Approx. Wall SF Comments	nediuriand Rim sea carpe  00 52 incir Pro est Fa	n densi ug Insti m tape et in adj EA h white light fix in and I	tute's Green L , tackless strip olning rooms.  ceiling fan Mo ture Model # Light Control w  Total:	with a abel os & metal Cover entire  SOU odel #  vired with
Install FHA minimum of certification edge strips floor includ frade: 23  8017 Remove th B552QI-W P2620-30E separate strips cocation:	A approved, Nylon/Olefin blend cut pile weave carpet. Install over a 1/2" mof seams in both pad and carpet. Carpet and Pad must meet the Carpet and Stretch carpet to eliminate puckers, scallops & ripples. Include premiur at transition to resilient, tile or wood floors. New carpet to be seamed to ling closets. Owner's choice of color and style.  Electric  ENERGY STAR CEILING FAN LIGHT FIXTURE  1. The existing ceiling fan. Install an ENERGY STAR® approved Farmington of the Hat Home Depot with a ENERGY STAR® approved Progress Lighting Air EBWB at Home Depot switched at the room entrance by a Leviton Do it Be witching for the fan and light.  9. Front Bedroom  Approx. Wall SF. 0	nediuriand Rim sea carpe  00 52 incir Pro est Fa	n densi ug Insti m tape et in adj EA h white light fix in and I	tute's Green L , tackless strip oining rooms.  ceiling fan Me ture Model # Light Control w	with a abel os & metal Cover entire
Install FHA minimum of certification edge strips floor includ frade: 23  8017 Remove th B552QI-W P2620-30E separate strips cocation: Spec # Frade: 10  3345	A approved, Nylon/Olefin blend cut pile weave carpet. Install over a 1/2" mof seams in both pad and carpet. Carpet and Pad must meet the Carpet and Stretch carpet to eliminate puckers, scallops & ripples. Include premiur at transition to resilient, tile or wood floors. New carpet to be seamed to ling closets. Owner's choice of color and style.  Electric  ENERGY STAR CEILING FAN LIGHT FIXTURE  1. se existing ceiling fan. Install an ENERGY STAR® approved Farmington of the Hat Home Depot with a ENERGY STAR® approved Progress Lighting Ale BWB at Home Depot switched at the room entrance by a Leviton Do it Be witching for the fan and light.  9 Front Bedroom  Approx. Wall SE Competers  Spec  Quantification of the State of the Stat	nediumand Rimand	n densiug Instium tape et in adjustion and I	tute's Green L , tackless strip oining rooms.  ceiling fan Me ture Model # Light Control w  Total:  Celling/Floors  Unit Price	with a abel os & metal Cover entire  SOU odel #  vired with
Install FHA minimum of certification edge strips floor includ frade: 23  8017 Remove th B552QI-W P2620-30E separate strips cocation: Spec # Frade: 10  3345	A approved, Nylon/Olefin blend cut pile weave carpet. Install over a 1/2" mof seams in both pad and carpet. Carpet and Pad must meet the Carpet and Stretch carpet to eliminate puckers, scallops & ripples. Include premiur at transition to resilient, tile or wood floors. New carpet to be seamed to ling closets. Owner's choice of color and style.  Electric  ENERGY STAR CEILING FAN LIGHT FIXTURE  1. The existing ceiling fan. Install an ENERGY STAR® approved Farmington of the Hat Home Depot with a ENERGY STAR® approved Progress Lighting Aid EBWB at Home Depot switched at the room entrance by a Leviton Do it Be witching for the fan and light.  9-Front Bedroom  Approx. Wall SF Country  Carpentry	nediumand Rimand	n densiug Instium tape et in adjustion and I	tute's Green L , tackless strip oining rooms.  ceiling fan Me ture Model # Light Control w  Total:  Celling/Floors  Unit Price	with a abel os & metal Cover entire  SOU odel #  vired with
Install FHA minimum of certification edge strips floor includ frade: 23  8017 Remove th B552QI-W P2620-30E separate strips separate strips  Spec # Frade: 10  3345 Install flush frade: 23  7555	A approved, Nylon/Olefin blend cut pile weave carpet. Install over a 1/2" mof seams in both pad and carpet. Carpet and Pad must meet the Carpet and Stretch carpet to eliminate puckers, scallops & ripples. Include premiur at transition to resilient, tile or wood floors. New carpet to be seamed to ling closets. Owner's choice of color and style.  Electric  ENERGY STAR CEILING FAN LIGHT FIXTURE  1. se existing ceiling fan. Install an ENERGY STAR® approved Farmington of the Hat Home Depot with a ENERGY STAR® approved Progress Lighting Air EBWB at Home Depot switched at the room entrance by a Leviton Do it Be witching for the fan and light.  9-Front Bedroom  Spec  Quantification of the fan and light.  1. spec Spec Quantification of the fan and light.  OORFLUSH INT, HOLLOW CORE  1. spec Spec Spec Spec Spec Spec Spec Spec S	oo bid 2 bid of 2 bid	n densiug Instium tape et in adjustion and I	tute's Green L , tackless strip oining rooms.  ceiling fan Me ture Model # Light Control w  Total:  Celling/Floors  Unit Price	with a abel os & metal Cover entire  SOU odel #  vired with
Install FHA minimum of certification edge strips floor includ frade: 23  8017 Remove th B552QI-W P2620-30E separate strips separate strips  Spec # Frade: 10  3345 Install flush frade: 23  7555	A approved, Nylon/Olefin blend cut pile weave carpet. Install over a 1/2" mof seams in both pad and carpet. Carpet and Pad must meet the Carpet and Seams in both pad and carpet. Carpet and Pad must meet the Carpet and Seams in both pad and carpet. Carpet and Pad must meet the Carpet and Seams in both pad and carpet. Carpet and Pad must meet the Carpet and Seams in both pad and carpet. Carpet and Pad must meet the Carpet and Seams in both pad and carpet. Seams in both pad and carpet to be seamed to display the seams in both pad and style.  Electric  ENERGY STAR CEILING FAN LIGHT FIXTURE  1. See existing ceiling fan. Install an ENERGY STAR® approved Farmington seams in the s	nediumand Rimand	n densiug Instium tape et in adjustin and I cation  Latin and I cation  Latin and I cation  Latin and I cation  Latin and I cation  EA	tute's Green L , tackless strip oining rooms.  ceiling fan Me ture Model # Light Control w  Total:  Celling/Floors  Unit Price	with a abel os & metal Cover entire  SOU odel #  vired with

dress:	58 B	ancroft Street	Unit: U	nit 01			VBT 3974
cation: Spec	erigeo Partici	0 - Rear Bedroom Spec	Approx: Wa	II SF: 0 Quantity		eiling/Floor SF Unit Price	Total Price
ade:	10	Carpentry					
<b>2370</b> Repai	r seve	FLOOR-CUSTOM WOOD REPAIR ral loose floor boards in door entrance		1.00	AL ·	<u> </u>	300
<b>2795</b> Repla	ice bro	WINDOW REPAIR  bken and cracked glass with double s		1.00 place failed	EA seal bot	tom sash with	350 new sealed
glass 3345		DOORFLUSH INT, HOLLOW CO		2.00	EA		550
Instal	l flush	, hollow core, masonite door on exist	ing jamb. Include privacy lo		coutt ning Locatio		,
			,	osaaspalusos variado	SSSC actions carried	Ceiling/Floor S	F 04
ocation	The state of the s	11 - Bathroom	Approx W	Quantity		Unit Price	Total Price
Spec	10	Spec		Quantity	Onits	Unit Frice	Total Filce
holderade: 5567 Usin crac are l	III a cher.  19 g lead ked or oose,	Paint & Wallpaper  PREP & PAINT VACANT ROOM VOC  safe work practices remove & dispose plaster is to be repaired with a resecure or remove & replace with difface shall be done with appropriate	ry set consisting of two 24" t  w/ PAINTED TRIM-LOW  se of all loose material & du bedding coat of Durabond & rywall patch. Sanding of any	252,00 st prior to ir & fiberglass y surfaces o	SF  nstallation s mesh ta	n of new mater spe. If plaster 8	ials. All lath boards a lead-based
mett or sa pain stoo g/L; Mar Rule	nod. Fatin fir ting. A k colo Floor nagem	Prime as necessary to seal stains, ravish cut-in neatly to trim & at all come apply two coats of latex semi-gloss pars. All paints and primers must not e 100 g/L; Anti-corrosive 250 g/L. All arent District. www.aqmd.gov/rules/regof the Bay Area Air Quality Management	w plaster, etc. Paint ceilings rs & edges. Prep trim doors aint to cover completely & un xceed the following maximu dhesives must comply with F/reg11/r1168.pdf All caulks	two coats in and windo niformly. Co m VOC rec Rule 1168 c	n flat ceill ws by de plors are puirement of the Sou	ng white & wai -glossing paint the choice of this: Flats 50 g/L ath Coast Air C	lls in eggshell led trim prior to he owner from ; Non-flats 50 tuality
Frade:			LIFET COORD	90.00	n er		BUO
on o	all 1/4 center ds w/	UNDERLAYMENT AND VINYL S  " underlayment grade plywood using allowing a 1/4" gap at wall. Fill seam minimum seams, per manufact, record color.	7d screw shank or cement on swith a manufacturer appro	oved filler.	s, or narro Install 07	0" thick, backe	d vinyl sheet
Trade:	22	Plumbing					
1) l dra htt leve	plumb nstall in) or t p://ww er sho	BATH—3 FIXTURE COMPLETE of entire bath to provide fixtures as folion 5', 4 piece, Sterling Advantage™, fiction 1030116 (left hand drain) Including a w.sterlingplumbing.com/home.strl - of wer diverter, shower rod and Delta Mead with a maximum 2.0 GPM flow recognition 103011.	berglass tub and shower un age in place factory installed complete with lever operated onitor Model 1343 tub/show	l backers fo I pop up dra er faucet - l	x 72" Pro or later gra ain and o http://www	ab bar installat verflow, PVC v v.deltafaucet.c	ion vaste, single com/ - and a

Exterior wall sections behind the tub shower unit and any plumbing penetrations must be completely air-sealed prior to

7590 RECEPTACLEGFCI BATH Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model # EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE-CONTINUOUS MODULATING-MOTION DETECTOR SWITCH Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE	rade: 22 Plumbing  Installation. Per installation Instructions set basin area in 1" to 2" of mortar cement. 2)Install a 1.28 GPF white American Standard FloWise Compact Cadet 3 EL 2568.128. Commode must be ADA height and a WaterSense® Certified, vibrous china commode tested through the latest edition of the "Maximum Performance" (MaP) testing project that has shown to score 800 or better on the MaP Flush Performance test (grams of solid waste removed in a single flush). See the following link for the MaP Test Results: http://www.cuwcc.org/MaPTesting.aspx include a manufacturer's approved plastic or pressed wood white seat, supply pipe, shut-off valve and wax seal. 3) Install a 24" plywood varity; including top with backsplash, wash bowl and single lever brass bodied chrome faucet with a maximum 1.5 GPM flow rate. Include PVC drain attached to a code legal plumbing vent, use type 1. copper or PEX supply piping with brass bodied stops, and escutcheon plates on all supply and waste lines. Cabinets must comply with California 93120 (formaldehyde content) or all exposed edges must be sealed with a low-VOC sealant.  rade: 23 Electric  7690 RECEPTACLE-GFCI BATH Install a flush mounted, ground fault circuit interrupted lvory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE  1.00 EA  6.00  Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model # EL-20G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS  1.00 EA  6.00  Install a Panasonic Whisper Green-Lite Model # FV-08VKMI.3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by ab built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented with any operating at less than .3 Sones, switched by	rade: 22 Plumbing  Installation. Per installation instructions set basin area in 1" to 2" of mortar cement. 2) Installa 1.28 GPF white American Standard FloWise Compact Caded 3 EL 2588.128. Commode must be ADA height and a WaterSense® Certified, vibrous china commode tested through the latest edition of the "Maximum Performance" (MaP) testing project that has shown to score 800 or better on the MaP Flush Performance test (grams of solid waste removed in a single flush). See the following link for the MaP Test Results: http://www.cuxcc.org/MaPTesting.aspx include a manufacturer's approved plastic or pressed wood white seat; supply pipe, shut-off valve, and wax seal. 3) Install a 24" plywood vanity, including top with backsplash, wash bowl and single lever brass bodied chrome faucet with a maximum 1.5 GPM flow rate. Include PVC drain attached to a code legal plumbing vent, use type. L copper or PEX supply piping with brass bodied stops, and escutcheon plates on all supply and waste lines. Cablinets must comply with California 93120 (formaldehyde content) or all exposed edges must be sealed with a low-VOC sealant.  rade: 23 Electric  7690 RECEPTACLE-GFCI BATH 1.00 EA	rade: 22 Plumbing  Installation. Per installation instructions set basin area in 1" to 2" of mortar cement.  2) Installa 1.28 GPF white American Standard FloWise Compact Cadet 3 EL 2588.128. Commode must be ADA height and a WaterSense® Cartified, vitreous china commode tested through the latest edition of the "Maximum Performance" (MaP) testing project that has shown to score 800 or better on the MaP Flush Performance test (grams of solid waste removed in a single flush). See the following link for the MaP Test Results: http://www.cuwcc.org/MaPresting.aspx include a manufacturer's approved plastic or pressed wood white seat; supply pips, shut-off valve, and wax seal.  3) Install a 24" plywood vanity, including top with backsplash, wash bowl and single lever brass bodied chrome faucet with a maximum 1.5 GPM flow rate. Include PVC drain attached to a code legal plumbing vent, use type, and wax seal.  3) Install a 5PM flow rate. Include PVC drain attached to a code legal plumbing vent, use type, and was seal.  3) Install a flush mounted, ground fault circuit interrupted looy duplex receptacle with looy-VOC sealant.  4 Flow rate in a sea of the sea of
installation. Per installation instructions set basin area in 1" to 2" of mortar cement. 2)Install a 1.28 GPF white American Standard FloWise Compact Cadet 3 EL 2568.128. Commode must be ADA height and a WaterSense® Certified, vitreous china commode tested through the latest edition of the "Maximum Performance" (MaP) testing project that has shown to score 800 or better on the MaP Flush Performance test (grams of solid waste removed in a single flush). See the following link for the MaP Test Results: http://www.cuwcc.org/MaPTesting.aspx Include a manufacturer's approved plastic or pressed wood white seat, supply pipe, shut-10f valve, and wax seal. 3) Install a 24" plywood vanity, including top with backsplash, wash bowd and single lever brass bodied chrome faucet with a maximum 1.5 GPM flow rate. Include PVG drain attached to a code legal plumbing vent, use type L copper or PEX supply piping with brass bodied stops, and escutcheon plates on all supply and waste lines. Cabinets must comply with California 93120 (formaldehyde content) or all exposed edges must be sealed with a low-VOC sealant.  **Trade: 23 Electric**  7590 RECEPTACLE-GFCI BATH	installation. Per installation instructions set basin area in 1" to 2" of mortar cement.  2)Install a 1.28 GPF white American Standard FloWise Compact Cadet 3 EL 2568.128. Commode must be ADA height and a WaterSense® Certified, vitreous china commode tested through the lattest edition of the "Maximum Performance" (MaP) testing project that has shown to score 800 or better on the MaP Flush Performance test (grams of solid waste removed in a single flush). See the following link for the MaP Test Results: http://www.cuvcc.org/MaPTesting.aspx Include a manufacturer's approved plastic or pressed wood white seat, supply pipe, shut-off valve, and wax seal.  3) Install a 24" plywood vanity, including top with backsplash, wash bowl and single lever brass bodied chrome faucet with a maximum 1.5 GPM flow rate. Include PVC drain attached to a code legal plumbing vent, use type L copper or PEX supply piping with brass bodied stops, and escutcheon plates on all supply and waste lines. Cabinets must comply with California as 120 (formaldehyde content) or all exposed edges must be sealed with a low-VOC sealant.  7590 RECEPTACLE—GFCI BATH	installation. Per installation instructions set basin area in 1" to 2" of mortar cement.  2)Install a 1.28 GPF white American Standard FloWise Compact Caded 3 EL 2588.128. Commode must be ADA height and a WaterSense® Certified, vitrous china commode fested through the latest edition of the "Maximum Performance" (MaP) testing project that has shown to score 800 or better on the MaP Flush Performance test (grams of solid waste removed in a single flush). See the following link for the MaP Test Results: http://www.cuxcc.org/MaPTesting.aspx include a manufacturer's approved plastic or pressed wood white seat, supply pipe, shut-off valve, and wax seal.  3) Install a 24" plywood vanlty, including top with backsplash, wash bowl and single lever brass bodied chromer faucet with a maximum 1.5 GPM flow rate. Include PVC drain attached to a code legal plumbing vent, use type L copper or PEX supply piping with brass bodied stops, and escutcheon plates on all supply and waste lines. Cabinets must comply with California 93120 (formaldehyde content) or all exposed edges must be sealed with a low-VOC sealant.  7690	installation. Per installation instructions set basin area in 1" to 2" of mortar cement.  2)Install a 1.28 GPF white American Standard FloWise Compact Cadet 3 EL 2568.128. Commode must be ADA height and a WaterSense® Certified, vitreous china commode tested through the latest edition of the "Maximum Performance" (MaP) testing project that has shown to score 800 or better on the MaP Flush Performance test (grams of solid waste removed in a single flush). See the following link for the MaP Test Results: http://www.cuwcc.org/MaPTesting.aspx Include a manufacturer's approved plastic or pressed wood white seat, supply pipe, shut-off valve, and wax seal.  3) Install a 24" plywood vanity, including top with backsplash, wash bowl and single lever brass bodied chrome faucet with a maximum 1.5 GPM flow rate. Include PVC drain attached to a code legal plumbing vent, use type L copper or PEX supply piping with brass bodied stops, and escutcheon plates on all supply and waste lines. Cabinets must comply with California 93120 (formaldehyde content) or all exposed edges must be sealed with a low-VOC sealant.  7590 RECEPTACLE-GFCI BATH  Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE  1.00 EA  ENERGY STAR 2 BULB BATH VANITY FIXTURE  1.00 EA  ENERGY STAR 2 BULB BATH VANITY FIXTURE  1.00 EA  ENERGY STAR 2 BULB BATH VANITY FIXTURE  1.00 EA  ENERGY STAR 2 BULB BATH VANITY FIXTURE and the search as Efficient Lighting's Model # EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE-CONTINUOUS  1.00 EA  ENERGY STAR 2 qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than 3 Sones, switched by a built in motion defector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, venited with a modulating DC motor capable of 80 CFM operating at
Zijinstala 1.26 PF White American Standard FloWise Compact Cadet 3 EL 2568.128. Commode must be ADA height and a WaterSense® Certified, vitreous china commode tested through the latest edition of the "Maximum Performance" (MaP) testing project that has shown to score 800 or better on the MaP Flush Performance test (grams of solid waste removed in a single flush). See the following link for the MaP Test Results: http://www.curxcc.org/MaPTesting.aspx include a manufacturer's approved plastic or pressed wood white seat, supply pipe, shut-off valve, and wax seal.  3) Install a 24" plywood vanity, including top with backsplash, wash bowl and single lever brass bodied chrome faucet with a maximum 1.5 GPM flow rate. Include PVC drain attached to a code legal plumbing vent, use type L copper or PEX supply piping with brass bodied stops, and escutcheon plates on all supply and waste lines. Cabinets must comply with California 93120 (formaldehyde content) or all exposed edges must be sealed with a low-VOC sealant.  rade: 23 Electric  7590 RECEPTACLE-GFCI BATH  1.00 EA  Electric  7590 RECEPTACLE-GFCI BATH  1.00 EA  GOO  Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE  1.00 EA  Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model #  EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS  MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CPM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a presset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to	Avairstall a 1.26 PP Write American Standard FloWise Compact Cadet 3 EL 2568.128. Commode must be ADA height and a WaterSense® Certified, vitreous china commode tested through the latest edition of the "Maximum Performance" (MaP) testing project that has shown to score 800 or better on the MaP Flush Performance test (grams of solid waste removed in a single flush). See the following link for the MaP Test Results: http://www.cuwcc.org/MaPTesting.aspx include a manufacturer's approved plastic or pressed wood white seat, supply pipe, shut-off valve, and wax seal.  3) Install a 24" plywood vanity; including top with backsplash, wash bowl and single lever brass bodied chrome faucet with a maximum 1.5 GPM flow rate. Include PVC drain attached to a code legal plumbing vent, use type L copper or PEX supply piping with brass bodied stops, and escutcheon plates on all supply and waste lines. Cabinets must comply with California 3120 (formaldehyde content) or all exposed edges must be sealed with a low-VOC sealant.  **Table 1.00 EA	2) install a 1.28 GPF White American Standard FloWise Compact Cadet 3 EL 2568.128. Commode must be ADA height and a WaterSense® Criffied, vitreous china commode tested through the latest edition of the "Maximum Performance" (MaP) testing project that has shown to score 800 or better on the MaP Flush Performance test (grams of solid waste removed in a single flush). See the following link for the MaP Test Results: http://www.cuwcc.org/MaPTesting.aspx include a manufacturer's approved plastic or pressed wood white seat, supply pipe, shut-off valve, and wax seal.  3) Install a 24" plywood vanity; including top with backsplash, wash bowl and single lever brass bodied chrome faucet with a maximum 1.5 GPM flow rate. Include PVC drain attached to a code legal plumbing vent, use type L copper or PEX supply piping with brass bodied stops, and escutcheon plates on all supply and waste lines. Cabinets must comply with California 3120 (formaldehyde content) or all exposed edges must be sealed with a low-VOC sealant.  **Receptacle—GFCI BATH**  Install a flush mounted, ground fault circuit interrupted livery duplex receptacle with invery cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  **Receptacle—Fish wire and repair all tear out.**  **Receptacle—Fish wire are a repair and repair and tear out.**  **Receptacle—Fish wire are a repair and repair and tear out.**  **Receptacle—Fish wire are a repair and repair and tear out.**  **Receptacle—Fish wire are a receptacle with interrupted livery and receptacle wire are a receptacle	Avairstant a 1.26 Pt White American Standard FloWise Compact Cadet 3 EL 2568.128. Commode must be ADA height and a WaterSense® Certified, vitreous china commode tested through the latest edition of the "Maximum Performance" (MaP) testing project that has shown to score 800 or better on the MaP Flush Performance test (grams of solid waste removed in a single flush). See the following link for the MaP Test Results: http://www.cuxcc.org/MaPTesting.aspx include a manufacturer's approved plastic or pressed wood white seat, supply pipe, shut-off valve, and wax seal.  3) Install a 24" plywood vanity; including top with backsplash, wash bowl and single lever brass bodied chrome faucet with a maximum 1.5 GPM flow rate. Include PVC drain attached to a code legal plumbing vent, use type L copper or PEX supply piping with brass bodied stops, and escutcheon plates on all supply and waste lines. Cabinets must comply with California 93120 (formaldehyde content) or all exposed edges must be sealed with a low-VOC sealant.  **Table 1.00 EA**    Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.    Treat
Trade: 23 Electric  Trade: 23 Electric  Trade: 23 Electric  Trade: RECEPTACLE-GFCI BATH Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  Trade: ENERGY STAR 2 BULB BATH VANITY FIXTURE Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model # EL-205G-223 installed above the sink.  TRE21 FAN/LIGHT FIXTURE—CONTINUOUS MODULATING-MOTION DETECTOR SWITCH Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Ocation: 12-Attic  Approx: Wall SE 0 Ceiling/Floor SE 0.  Spec # Spec Quantity Units Unit Price Total Price  Trade: 7 Masonry	RECEPTACLE—GFCI BATH Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  The standard of the st	RECEPTACLE—GFCI BATH Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and repair all tear out.  The substituting copper non-metallic cable. Fish wire and substituting copper non-metallic cable. Fish substituting copper non-metallic cable. Fish wire and substituting copper non-metallic cable. Fish substituting cable and substituting cable a	Processor of the continuous of the continuous of the continuous of the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Processor of Masonry  1335 CHIMNEY-REPAIR CHASE  1.00 AL  1.00 EA  1
Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE  Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model #  EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS  MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Celling/Floor SF 0  Spec # Spec Quantify Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE	Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE 1.00 EA 6000 Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model # EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS 1.00 EA 6000 Install a Panasonic Whisper Green-Lite Model # FY-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE 1.00 AL 2000	Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE 1.00 EA 60.00 Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model # EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS 1.00 EA 60.00 Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Celling/Floor SF 0  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY—REPAIR CHASE 1.00 AL 2000	Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE 1.00 EA 6000 Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model # EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS 1.00 EA 6000 Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Cocation: 12 - Attic ADDIOX Wall SE 0 Ceiling/Floor SF 0  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE 1.00 AL 2000
Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE 1.00 EA Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model # EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS 1.00 EA MODULATING-MOTION DETECTOR SWITCH Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:    Ceiling/Floor SF 0	Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE 1.00 EA Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model # EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS 1.00 EA MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE 1.00 AL 1000	Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE 1.00 EA Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model # EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS 1.00 EA MODULATING-MOTION DETECTOR SWITCH Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Cation Total:  Approx Wall SE 0. Ceiling/Floor SE 0.  Spec # Spec  Quantity Units Unit Price Total Price  Total Price  Tade: 7 Masonry  1335 CHIMNEY—REPAIR CHASE  Install missing brick in chimney chase in attic area.	Install a flush mounted, ground fault circuit interrupted ivory duplex receptacle with ivory cover plate adjacent to lavatory using copper non-metallic cable. Fish wire and repair all tear out.  7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE 1.00 EA Lighting's Model # EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS 1.00 EA MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foll faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE 1.00 AL 2000
T761 ENERGY STAR 2 BULB BATH VANITY FIXTURE  Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model #  EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS  MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than 3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Celling/Floor SF 0  Spec # Spec Quantity Units Unit Price Total Price Trade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE	7761 ENERGY STAR 2 BULB BATH VANITY FIXTURE 1.00 EA	T761 ENERGY STAR 2 BULB BATH VANITY FIXTURE 1.00 EA	T761 ENERGY STAR 2 BULB BATH VANITY FIXTURE 1.00 EA
Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model #  EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS  MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Ceiling/Floor SF 0  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE	Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model #  FL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS  MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion defector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:    Cocation Total:	Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model #  FL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS  MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE 1.00 AL 2000  Install missing brick in chimney chase in attic area.	Install an Energy Star approved, over vanity light fixture using GU24 base lamps such as Efficient Lighting's Model #  EL-205G-223 installed above the sink.  7821 FAN/LIGHT FIXTURE—CONTINUOUS  MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE Install missing brick in chimney chase in attic area.
FAN/LIGHT FIXTURE—CONTINUOUS  MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:    Ceiling/Floor.SF 0	FAN/LIGHT FIXTURE—CONTINUOUS MODULATING-MOTION DETECTOR SWITCH Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a walf or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Location Total:  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY—REPAIR CHASE  Install missing brick in chimney chase in attic area.	FAN/LIGHT FIXTURE—CONTINUOUS MODULATING-MOTION DETECTOR SWITCH Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than 3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:    Location Total:	FAN/LIGHT FIXTURE—CONTINUOUS MODULATING-MOTION DETECTOR SWITCH Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a walf or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Location Total:  Spec # Spec
FAN/LIGHT FIXTURE—CONTINUOUS  MODULATING—MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Celling/Floor.SE 0.  Spec # Spec	FAN/LIGHT FIXTURE—CONTINUOUS MODULATING-MOTION DETECTOR SWITCH Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a walf or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Location Total:  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY—REPAIR CHASE  Install missing brick in chimney chase in attic area.	FAN/LIGHT FIXTURE—CONTINUOUS MODULATING-MOTION DETECTOR SWITCH Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than 3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:    Location Total:	FAN/LIGHT FIXTURE—CONTINUOUS MODULATING-MOTION DETECTOR SWITCH Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a walf or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:    Location Total:
Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Ceiling/Floor SE 0  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE	MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a walf or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:    Location Total:	MODULATING-MOTION DETECTOR SWITCH  Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Location Total:    Location Total:	Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than 3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Spec # Spec
Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:  Ceiling/Floor SE 0  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  CHIMNEY-REPAIR CHASE	Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:    Location Total:	Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:    Location Total:	Install a Panasonic Whisper Green-Lite Model # FV-08VKML3 ceiling mounted, ENERGY STAR qualified Fan/Light fixture with a modulating DC motor capable of 80 CFM operating at less than .3 Sones, switched by a built in motion detector and night light, the capacity to run continuously at a preset CFM rating, a time delay feature for the boost setting, vented w/ damper to exterior. Install 4" galvanized metal duct (not flex duct) and vent to the exterior ideally through a wall or gable end using a 4" hooded vent with damper. All duct seams and connections shall be sealed with duct mastic. Insulate the ductwork with vinyl or foil faced R 8 minimum duct insulation. Repair any damage to the ceiling installation and air seal fan/light assembly to the ceiling with low VOC caulk. Set the continuous level of ventilation to meet ASHRAE 62.2 and set the time delay switch to 20 minutes.  Location Total:    Location Total:
ocation: 12-Attic Approx Wall SE 0 Ceiling/Floer SE 0  Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE	Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE Install missing brick in chimney chase in attic area.	Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE Install missing brick in chimney chase in attic area.	Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE Install missing brick in chimney chase in attic area.
Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE 1.00 AL 2000	Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE 1.00 AL	Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE 1.00 AL	Spec # Spec Quantity Units Unit Price Total Price rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE 1.00 AL
rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE  1 00 Al 2000	rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE Install missing brick in chimney chase in attic area.	rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE Install missing brick in chimney chase in attic area.  rade: 10 Carpentry  1.00 AL  200  1.00 AL	rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE Install missing brick in chimney chase in attic area.
rade: 7 Masonry  1335 CHIMNEY-REPAIR CHASE 1.00 Al 2000	1335 CHIMNEY-REPAIR CHASE Install missing brick in chimney chase in attic area.	1335 CHIMNEY-REPAIR CHASE Install missing brick in chimney chase in attic area.  rade: 10 Carpentry	1335 CHIMNEY-REPAIR CHASE Install missing brick in chimney chase in attic area.
	Install missing brick in chimney chase in attic area.	Install missing brick in chimney chase in attic area.	Install missing brick in chimney chase in attic area.
	Install missing brick in chimney chase in attic area.	Install missing brick in chimney chase in attic area.  rade: 10 Carpentry -	Install missing brick in chimney chase in attic area.
merali miesnių drick ir chimney chase in attic area.	rade: 10 Carpentry		rade: 10 Carpentry
rade: 10 Carpentry	2520 HANDRAIL BERLACE INTERIOR	2520 HANDRAII PEDIACE INTEDIOR	2520 HANDRAIL DEDLACE INTERIOR
2520 HANDDAN DEDLACE INTERIOR			
2520 HANDRAIL—REPLACE INTERIOR  Install 2" round hardwood handrail screwed to metal handrail braces that are attached to studs with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the result of the plumb with the result of	Install 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the control of the plastic masonry plug fasteners and	fristall 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the annual factor of the plumb with the annual factor.	Install 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the annual factor of the plumb with the plumb
2520 HANDRAIL—REPLACE INTERIOR  Install 2" round hardwood handrail screwed to metal handrail braces that are attached to studs with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the result of the plumb with the result of	Install 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the control of the plastic masonry plug fasteners and	fristall 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the annual factor of the plumb with the annual factor.	Install 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the annual factor of the plumb with the plumb
HANDRAIL—REPLACE INTERIOR  Install 2" round hardwood handrail screwed to metal handrail braces that are attached to studs with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.	Install 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.  3515 ATTIC GUARD RAIL REPAIR-WOOD	framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.  3515 ATTIC GUARD RAIL REPAIR-WOOD	Install 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.  3515 ATTIC GUARD RAIL REPAIR-WOOD
HANDRAIL—REPLACE INTERIOR  Install 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.  3515  ATTIC GUARD RAIL REPAIR-WOOD  4.00 LF  GOOD  Replace missing or defective balusters, support posts and railing with same size stock.	Install 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.  3515 ATTIC GUARD RAIL REPAIR-WOOD  4.00 LF  GOOD  Replace missing or defective balusters, support posts and railing with same size stock.	framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.  3515 ATTIC GUARD RAIL REPAIR-WOOD  4.00 LF  Replace missing or defective balusters, support posts and railing with same size stock.	Install 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.  3515 ATTIC GUARD RAIL REPAIR-WOOD  4.00 LF  SOO  Replace missing or defective balusters, support posts and railing with same size stock.
2520 HANDRAIL—REPLACE INTERIOR  Install 2" round hardwood handrail screwed to metal handrail braces that are attached to studs with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.  3515 ATTIC GUARD RAIL REPAIR-WOOD  4.00 LF  GOOD  GEORGIA STREET OF ST	Install 2" round hardwood handrail screwed to metal handrail braces that are attached to study with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.  3515 ATTIC GUARD RAIL REPAIR-WOOD  4.00 LF  GOOD  Replace missing or defective balusters, support posts and railing with same size stock.	framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.  3515 ATTIC GUARD RAIL REPAIR-WOOD  4.00 LF  Replace missing or defective balusters, support posts and railing with same size stock.	Install 2" round hardwood handrail screwed to metal handrail braces that are attached to studs with screws that enter the framing at least 1 inch, or if fastening to a masonry wall use minimum 3/8 inch diameter plastic masonry plug fasteners and compatible screws. Handrail will extend 6 inches past a line plumb with the nosing of the top tread and 6 inches past a line plumb with the nosing of the bottom tread. All edges will be eased to a smooth and rounded condition.  3515 ATTIC GUARD RAIL REPAIR-WOOD  4.00 LF  Replace missing or defective balusters, support posts and railing with same size stock.
Install missing brick in obting a state of the state of t	Install missing brick in chimney chase in attic area.	rade: 10 Carpentry	Install missing brick in chimney chase in attic area.
and the same of th			
rade: 10 Camento			

Page 9 of 10.

Address:	58	Bancroft Street		Unit: Un	it 01			4.B.T 7-9-18
Location: Spec		13 - Stairs Spec		Approx Wal		A CONTRACTOR OF THE PARTY OF THE PARTY.	Ceiling/Floor S Unit Price	SCHOOLSTELLERATE TO A SECURE A SECURE
Trade:	10	Carpentry			•		<u>, , , , , , , , , , , , , , , , , , , </u>	
<b>2520</b> Repai	r loos	HANDRAIL-REPAII se handrailing and balu	R INTERIOR esters on main staircase.		1.00	AL		500
		Santa Sa	and the state of the		ı	_ocatio	n Total:	
			Unit To	tal for 58 Bancre	oft Stree	t, Unit	Unit 01:	
			Addre	ess Grand Total f	or 58 B	ancroft	Street:	·
				Bidder:				

635°5-



Bill To COMMUNITY DEVELOPMENT 1600 EAST COLUMBUS AVE

SPRINGFIELD, MA 01107

Acct No: 26451815-530105-64516

SPRINGFIELD, MA

USA Tel#886-5050

01103

Review:

Buyer: lpl Status: Released

Page 1

FY 2019

Vendor
KRISTIAN BERRIOS TORRES & MANSABEL GONZ COMMUNITY DEVELOPMENT
58 BANCROFT ST 1600 EAST COLUMBUS AVE

SPRINGFIELD, MA 01103 NGREAVES@SPRINGFIELDCITYHALL.COM

Reguisition 19006683-00

Delivery Reference NIGEL GREAVES

( #20190357

Date Ordered	Vendor Number	Date Required	Ship Via	Terms	Department	
11/07/18	018470	1	ĺ		COMMUNITY DEVELO	OPMENT
LN Descript	ion / Acc	ount	***************************************	Qty	Unit Price	Net Price
General	Notes					
001 CDBG-NDF	LOCATED	HOMES REHA AT 58 BANC		1.00 EAC		70965.00
1 2645181	L5-530105-	64516			70965.00	
36 COURT ROOM 405 SPRINGFI	T STREET 5/411 EELD, MA 7 Referenc	4TH FLOOR				

## Requisition Link

Requisition Total

70965.00

\*\*\*\* General Ledger Summary Section \*\*\*\*\* Account 26451815-530105-64516 CDBG-NDR-HEALTH HOMES Remaining Budget 3951730.66 Amount 70965.00 PROFESSIONAL SERVICES

\*\*\*\*\* Approval/Conversion Info \*\*\*\*\*
Activity Date Clerk
Approved 11/07/18 Amanda Pham
Approved 11/07/18 Cathy Buono

Comment Auto approved by: cak



Bill To COMMUNITY DEVELOPMENT 1600 EAST COLUMBUS AVE

Acct No: 26451815-530105-64516

SPRINGFIELD, MA

Review:

01103

Buyer: lpl Status: Released

Page 2

FY 2019

Vendor
KRISTIAN BERRIOS TORRES & MANSABEL GONZ COMMUNITY DEVELOPMENT
58 BANCROFT ST 1600 EAST COLUMBUS AVE

SPRINGFIELD, MA 01107

USA Tel#886-5050

SPRINGFIELD, MA 01103 NGREAVES@SPRINGFIELDCITYHALL.COM

Requisition 19006683-00

Delivery Reference NIGEL GREAVES

Date Ordered		Date Required	Ship Via	Terms		Department		
11/07/18	018470					COMMUNITY DEVEL	DPMENT	_
LN Descripti Queued Queued Queued Queued Queued Pending Pending Pending	on / Acco 11/07/1 11/07/1 11/07/1 11/07/1 11/07/1	8 Hamedi 8 Melani 8 Christ 8 Heathe 8 Tim Br TJ Pla Lindsa		ser	Qty	Unit Price	Net	Price